

# DSC

*From Tyco Security Products*



## PRODUCT CATALOG 2017 • 2018



Wherever you are,  
you can rely on **DSC**  
to bring home closer.



## Interactive with DSC, it's simply a matter of choice

A selection of quality security products by DSC are now compatible with leading-edge solutions offered by trusted interactive service experts.

Maximize the full potential of your security system with a variety of smart home control and monitoring features offered through DSC's interactive service partner, Alarm.com.

It's reliability, flexibility and service excellence at it's finest.

For more information on available features and packages, talk to your security professional or visit [www.dsc.com](http://www.dsc.com).

**A world of interactive choice – with DSC**



# DSC

From Tyco Security Products

# Contents

catalog 2017 | 18

■ <b>HYBRID SOLUTIONS</b>	<b>3</b>
POWERSERIES NEO . . . . .	4
DNA Chart . . . . .	4
Panels. . . . .	6
Panels Comparison Chart . . . . .	7
Keypads . . . . .	8
Modules. . . . .	10
Communication . . . . .	11
PowerG - Intrusion . . . . .	12
PowerG - Safety . . . . .	15
PowerG - Sirens & Repeaters . . . . .	18
POWERSERIES . . . . .	19
DNA Chart . . . . .	19
Panels. . . . .	20
Keypads . . . . .	22
Modules. . . . .	26
Communication . . . . .	29
MAXSYS . . . . .	30
Panels & Keypads. . . . .	30
Modules. . . . .	31
Receivers & Transmitters . . . . .	32
Accessories . . . . .	33
■ <b>WIRELESS SOLUTIONS</b>	<b>34</b>
DNA Chart . . . . .	35
Panels. . . . .	36
Keypads . . . . .	37
Communication . . . . .	38
SENSORS & ACCESSORIES . . . . .	39
Intrusion. . . . .	40
Arming Devices . . . . .	41
Safety . . . . .	42
Sirens . . . . .	43
■ <b>UNIVERSAL COMMUNICATORS SOLUTIONS</b>	<b>45</b>
Transmitters. . . . .	46
■ <b>HARDWIRED SOLUTIONS</b>	<b>49</b>
Intrusion. . . . .	50
Intrusion & Accessories . . . . .	56
Safety . . . . .	57
Repeaters & Modules . . . . .	58
Addressable. . . . .	59
■ <b>CENTRAL MONITORING STATION SOLUTIONS</b>	<b>61</b>
Sur-Gard Receivers . . . . .	62
■ <b>SOFTWARE SOLUTIONS &amp; SERVICES</b>	<b>64</b>
Software . . . . .	65
Service & Support. . . . .	67
■ <b>INDEX</b>	<b>68</b>



PowerSeries  
**neo**

Expand  
your  
Horizons



Infused with industry-leading PowerG 2-way wireless communication, PowerSeries Neo's unique combination of trusted hybrid and wireless technologies provides a myriad of installation options.

Adaptable, highly secure PowerG wireless devices and peripherals can be installed in even the toughest locations – shaving hours off a job and significantly reducing complexity. Dealers benefit from decreased operational costs while providing a multitude of expansion possibilities for residential through to scalable commercial installations.

**Welcome to Security Redefined.**

with  
**PowerG**  
Technology



**DSC**  
From Tyco Security Products

Hybrid Solutions



x = frequency - 915 MHz, 433 MHz, 868 MHz
915 MHz = NORTH AMERICA, LATAM, CARIBBEAN
433 MHz = AFRICA, ASIA, AUSTRALIA, EASTERN EUROPE, BRAZIL, PERU, URUGUAY, NEW ZEALAND
868 MHz = AFRICA, EASTERN EUROPE, WESTERN EUROPE, UK, MIDDLE EAST

### Intrusion Detectors



Security



PGx934P  
Wireless PowerG PIR Motion Detector with Integrated Camera



PGx944  
Wireless PowerG Outdoor PIR Motion Detector with Integrated Camera



PGx924  
Wireless PowerG Curtain PIR Motion Detector



PGx984P  
Wireless PowerG Dual Technology (PIR & MW) Motion Detector



PGx974P  
Wireless PowerG Mirror Optic PIR Motion Detector



PGx994  
Wireless PowerG Outdoor PIR Motion Detector



PGx975  
Wireless PowerG Door/Window Contact in White or Brown



PGx945  
Wireless PowerG Door/Window Contact with Auxiliary Input, in White or Brown



PGx935  
Wireless PowerG Shock Detector



PGx922  
Wireless PowerG Glass Break Detector

### Safety Sensors



Safety



PGx926  
Wireless PowerG Smoke Detector



PGx916  
Wireless PowerG Smoke and Heat Detector



PGx913  
Wireless PowerG CO Detector



PGx905  
Wireless PowerG Temperature Detector



PGx985  
Wireless PowerG Flood Detector

### Arming Devices & Panic Buttons



Remote Control



PGx938  
Wireless PowerG Panic Key



PGx949  
Wireless PowerG 2-Button Key



PGx939  
Wireless PowerG 4-Button Key



PGx929  
Wireless PowerG 4-Button Key



MPT  
Mini Prox Tag

### Keypads



Remote Control



HS2LCDWFx / HS2LCDWFPx / HS2LCDWFPVx  
Wireless Full Message LCD PowerG 2-Way Wire-Free Keypad with optional Prox Support and Voice Prompting



HS2LCD / HS2LCDP  
Full Message LCD Keypad with optional Prox Tag Support



HS2ICN / HS2ICNP  
ICON Hardwired Keypad with optional Prox Tag Support



HS2LCDRFx / HS2LCDRFPx  
Full Message LCD Keypad with Built-in PowerG Transceiver with optional Prox Support



HS2ICNRFx / HS2ICNRFPx  
ICON Hardwired Keypad with Built-in PowerG Transceiver with optional Prox Support



HS2TCHP  
Hardwired Touchscreen Keypad 7 inch with Prox Support in Black or White

### Sirens, Repeaters & Transceivers



Sirens, Repeaters & Transceivers



PGx901  
Wireless PowerG Indoor Siren



PGx911  
Wireless PowerG Outdoor Siren



PGx920  
Wireless PowerG Repeater



HSM2HOSTx  
PowerG Host Transceiver Module

### Communicators & Transmitters



Communication



3G8080 / 3G8080(I)  
HSPA Cellular Alarm Communicator compatible with ALARM.COM



CD8080 / CD8080(I)  
CDMA Cellular Alarm Communicator compatible with ALARM.COM



3G2080E / 3G2080RE  
HSPA Cellular Alarm Communicator (optional serial connection for integration)



TL2803GE / TL2803GRE  
Internet and HSPA Dual-path Alarm Communicator (optional serial connection for integration)



T280E / TL280RE  
Internet Alarm Communicator (optional serial connection for integration)



PCL-422  
Communicator Remote Mounting Module

### Modules



Module



HSM2300  
Power Supply Module



HSM2204  
High Current Output Module



HSM2208  
Low Current Output Module



HSM2955(R)  
Two-Way Audio Module



HSM2108  
8-Hardwired Zone Expander Module

### Software Support



Support



WebSA System Administrator Software



Routine System Management Software (RSM)




DLS 5 Downloading Software

### Control Panels



HS2016 / HS2032 / HS2064E / HS2128E  
6 to 128 zone control panel






HS2016 6 to 16 Zone

- 6 on-board zones
- Expandable to 16 wireless and hardwired zones
- 2 PGM outputs: expandable to 22 (HSM2204, HSM2208)
- Template programming

- Connect up to 8 supervised keypads with keypad zones
- 2 partitions
- 500-event buffer
- 48 user codes

Available in NA, LATAM, Europe, Africa and APAC




HS2016-4 8 to 32 Zone

- 8 on-board zones
- Expandable to 16 hardwired or 32 wireless zones
- 4 PGM outputs: expandable to 24 (HSM2204, HSM2208)
- Template programming

- Connect up to 8 supervised keypads with keypad zones
- 8 partitions
- 500-event buffer
- 48 user codes

Available in Africa




HS2032 8 to 32 Zone

- 8 on-board zones
- Expandable to 32 wireless and hardwired zones
- 2 PGM outputs: expandable to 38 (HSM2204, HSM2208)
- Template programming

- Connect up to 8 supervised keypads with keypad zones
- 4 partitions
- 500-event buffer
- 72 user codes

Available in NA, LATAM, Europe, Africa and APAC




HS2064 8 to 64 Zone

- 8 on-board zones
- Expandable to 64 wireless and/or hardwired zones
- 4 PGM outputs: expandable to 80 (HSM2204, HSM2208)
- Template programming

- Connect up to 8 supervised keypads with keypad zones
- 8 partitions
- 500-event buffer
- 500 user codes

Available in NA, LATAM, Europe, Africa and APAC



HS2128 8 to 128 Zone

- 8 on-board zones
- Expandable to 128 wireless and/or hardwired zones
- 4 PGM outputs: expandable to 148 (HSM2204, HSM2208)
- Template programming

- Connect up to 16 supervised keypads with keypad zones
- 8 partitions
- 1000-event buffer
- 1000 user codes

Available in NA, LATAM, Europe, Africa and APAC

PowerSeries Neo Feature Comparison Chart

Features	HS2016	HS2016-4	HS2032	HS2064	HS2128
Number of On-Board Zones	6	8	8	8	8
Total Zones Supported	16	32	32	64	128
Keypad Zone Expansion	Yes	Yes	Yes	Yes	Yes
Hardwired Zones	Yes	Yes	Yes	Yes	Yes
Wireless Zone Expansion	Yes	Yes	Yes	Yes	Yes
Number of Hardwired Keypads	8	8	8	8	16
Number of Wireless Keypads	8	8	8	8	16
Number of Wireless Receivers	1	1	1	1	1
Number or Wireless Repeaters	4	4	8	8	8
On-Board PGM Outputs	2	4	2	4	4
Number of Main Panel Low-Current PGM Outputs	1	1	1	1	1
Number of Main Panel High-Current PGM Outputs	1	3	1	3	3
PGM Expansion	Yes	Yes	Yes	Yes	Yes
Number of Additional High-Current PGM Outputs	4	4	4	12	16
Number of Additional Low-Current PGM Outputs	16	16	32	64	128
Number of Access Codes	47 + master	47+ Master	71 + master	499 + master	999 + master
Number of Partitions	2	8	4	8	8
Panel Event Buffer	500	500	500	500	1000
Phone Line Supervision	Yes	Yes	Yes	Yes	Yes
Siren Supervision	Yes	Yes	Yes	Yes	Yes
Bell Output	Yes	Yes	Yes	Yes	Yes
SIA CP-01 Compliant	Yes	No	Yes	Yes	Yes
SMS Command and Control	Yes	Yes	Yes	Yes	Yes
Upload/Download Support	Yes	Yes	Yes	Yes	Yes
Direct-Connect (PC Link) Downloading Support	Yes	Yes	Yes	Yes	Yes
DLS SA End-User Downloading Support	Yes	Yes	Yes	Yes	Yes
Internet Alarm Communications	Yes	Yes	Yes	Yes	Yes
Audio Alarm Verification	with HSM2955(R)	with HSM2955(R)	with HSM2955(R)	with HSM2955(R)	with HSM2955(R)
Cellular Alarm Communications	Yes	Yes	Yes	Yes	Yes
Battery Required	Yes	Yes	Yes	Yes	Yes





**HS2LCDWFPx Wireless Full Message LCD PowerG 2-Way Wire-Free Keypad**  
**HS2LCDWFPx With Prox Support**  
**HS2LCDWFPVx With Prox Support & Voice Prompting**

- 2 x16 full message display
- Intuitive clock programming
- Multiple door chime
- Blue display
- White keymat backlight
- Displays outdoor temperature with PGx905
- Voice Prompts
- Installer programming
- Multi-language support
- 5 programmable function keys
- Fire, Medical and Panic keys
- Available with English function keys
- Tamper switch
- Proximity with MPT mini prox tags

Available in NA, LATAM, Europe, Africa and APAC



**MPT Mini Prox Tag**

Chicklets are small proximity tags for easy arming and disarming of the system. They are ideal for premises with multiple users or infrequent users who may not remember the arm/disarm code.

- 8 different colors
- Keychain strap
- Easily arm and disarm the system
- Compatible with international standards
- Compatible with select control panels and keypads
- Can be placed on a keychain for convenient entry

Available in NA, LATAM, Europe, Africa and APAC



**HS2ICN ICON Hardwired Keypad**  
**HS2ICNP With Prox Support**  
**HS2ICNRFx With Built-in PowerG Transceiver**  
**HS2ICNRFPx With Built-in PowerG Transceiver & Prox Support**

- Up to 128 hardwired or wireless zones supported
- Modern, slim-line landscape keypad
- White backlit keys
- Blue LCD display
- 5 programmable function keys
- Input/Output terminal
- Fire, Medical and Panic keys
- Adjustable backlight and keypad buzzer
- Available with English function keys
- Proximity with MPT mini prox tags

Available in NA, LATAM, Eastern Europe and APAC

**HS2LCD Full Message LCD Hardwired Security Keypad**  
**HS2LCDP Full Message LCD Hardwired Keypad With Prox Support**  
**HS2LCDRFx Full Message LCD Hardwired Keypad With Built-in PowerG Transceiver**  
**HS2LCDRFPx Full Message LCD Hardwired Keypad With Built-in PowerG Transceiver & Prox Support**

- Multi-language support
- Global partition status
- Up to 128 hardwired or wireless zones supported
- Full 32-character programmable labels
- Menu programming
- Modern, slim-line landscape keypad
- White backlit keys
- Blue LCD display
- Displays outdoor temperature with PGx905
- 5 programmable function keys
- Intuitive clock programming
- Input/Output terminal
- Fire, medical and panic keys
- Adjustable backlight and keypad buzzer
- Dual wall-mount and front cover tamper
- Available with English function keys
- Proximity with MPT mini prox tags

Available in NA, LATAM, Europe, Africa and APAC



**HS2TCHP 7 inch Hardwired TouchScreen Keypad with Prox Support**

- Responsive, high-resolution 7" (177.8 mm) full color touchscreen
- Intuitive menu-driven interface for the user
- Configurable home screen
- Built-in and easy-to-update digital picture frame using integrated SD card slot
- Simplified programing of labels using QWERTY keypad
- Clean, low-profile case in either white or black blends into any décor
- Quick-view LED status indicators (Ready, Armed, Trouble and AC Power)
- Interactive Menu ready
- I/O terminal
- SD card GUI Local firmware update
- Prox support (using MPT prox tags)
- Multiple language support

Available in NA, LATAM, Europe, Africa and APAC



PowerSeries Neo Keypad Features	WIRE-FREE		HARDWIRED	
	LCD	LCD	ICON	TouchScreen
Built-in transceiver option		•	•	
Prox option	•	•	•	•
Voice prompt	•			
8 Partition Support	•	•	•	•
Front & rear mount tamper	•	•	•	•
5 Programmable function keys	•	•	•	•
3 Separate panic keys	•	•	•	•
Multiple door chimes	•	•	•	•
I/O onboard		•	•	•






HSM2HOSTx PowerG Host Transceiver Module

- Supports up to 128 wireless zones and 32 wireless keys – varies per panel
- Supports DSC PowerG devices
- Compatible with PGx920 PowerG Repeater for range extension
- All wireless detectors are fully supervised for communication integrity


Available in NA, LATAM, Europe, Africa and APAC



HSM2300 Power Supply Module

- Fully supervised for AC failure, low battery and AUX failure
- Provides up to 1 Amp @ 12 VDC


Available in NA, LATAM, Europe, Africa and APAC



HSM2204 High Current Output Module

- Fully supervised for AC failure, low battery and AUX failure
- 4 programmable high current voltage outputs: rated at 1 Amp @ 12 VDC
- Output #1 can be used as a supervised bell output
- Provides up to 1 Amp @ 12 VDC


Available in NA, LATAM, Europe, Africa and APAC



HSM2208 Output Module

- Provides 8 low current (50 mA) programmable outputs

Available in NA, LATAM, Europe, Africa and APAC



HSM2108 Hard wired zone expander

- Adds 8 hardwired zones
- AUX power up to 125 mA (PTC protected)


Available in NA, LATAM, Europe, Africa and APAC



HSM2955(R) Two-Way Audio Module

- Up to 4 two-way audio stations supported
- Optional recording of up to 15 minutes of pre-alarm activity
- Supports both 2-way audio VOX and push-to-talk verification
- Silent/Listen-in functionality on hold-up alarms (activates only when an alarm occurs)
- Two-way audio over PSTN or Cellular
- Supports PC5961E small and PC5964E large audio stations

Available in NA and EMEA



PCL-422 Communicator Remote Mounting Module

- Allows extension of the PC-LINK connection by 50 ft (15 m) so communicator can be mounted in separate enclosure from panel
- Distance can be extended up to 1000 ft (300 m) if additional power supply is used
- Compatible with 3G2080(E), TL2803G(E) and TL280(E) alarm communicators

Available in NA, LATAM, Europe, Africa and APAC

Approval Listing and Frequency vary depending on country. Please refer to [www.dsc.com](http://www.dsc.com) for complete listings and availability.

3G8080(I) / CD8080(I) PowerSeries Neo HSPA / CDMA Cellular Alarm Communicator

- 4 integrated communicator models: 3G8080; 3G8080I\*; CD8080\*\*; CD8080I\*/\*\*
- 2 integrated cellular technologies: HSPA (3G); CDMA\*\*
- Antenna Extension Kits available: GS-15ANTQ, GS-25ANTQ, GS-50ANTQ
- Signal strength and trouble display
- PC-Link connection
- Compatible with HS2016/ HS2032/ HS2064/ HS2128 control panels
- Compatible with Sur-Gard System I -IP/II/III/IV/5 monitoring station receivers
- Compatible with alarm.com

Available in NA, LATAM, Europe, Africa and APAC

\* Required for supporting image sensors      \*\* Only available in US

3G2080(R)E HSPA Cellular Alarm Communicator

- Back up and primary Cellular alarm communication
- Panel remote uploading/downloading support via Cellular
- Supervision heartbeats via Cellular
- 128-bit AES encryption via Cellular
- Full event reporting
- SIA and Contact ID protocol
- Remote activation and programming through C24 Communications (North America Only)
- Signal strength and trouble display
- Visual verification over Cellular
- Communicator can be housed in separate cabinet using PCL-422 Communicator Remote Mounting Module
- Command and Control via SMS
- R model includes RS232 serial integration option
- Provides expanded user support with PowerSeries Neo HS2064 and HS2128 panels V1.2 and higher

Available in NA, LATAM, Europe, Africa and APAC

TL2803G(R)E Internet and HSPA Dual-path Alarm Communicator

- Fully redundant Internet and Cellular dual-path alarm communication
- Integrated call routing
- Panel remote uploading/downloading support via Cellular and Internet
- Supervision heartbeats via Cellular and Internet
- 128-bit AES encryption via Cellular and Internet
- Full event reporting
- SIA and Contact ID protocol
- Remote activating and programming through C24 Communications (North America Only)
- Active Cellular account is required to use IP function
- Signal strength and trouble display
- Visual verification over Cellular or Internet
- Communicator can be housed in separate cabinet using PCL-422 Communicator Remote Mounting Module
- Command and Control via SMS
- R model includes RS232 serial integration option supports up to 4 integration paths over Ethernet
- Provides expanded user support and up to 4 ethernet integrations with PowerSeries Neo panels HS2064 and HS2128 V1.2 and higher


Available in NA, LATAM, Europe, Africa and APAC

T280(R)E Internet Alarm Communicator

- Panel remote uploading/downloading via Internet
- Programmable using DLS 5 or keypad
- Supervision heartbeat via Internet
- 128 Bit AES Encryption
- Full event reporting
- SIA and Contact ID protocol
- Visual verification over Internet
- Communicator can be housed in separate cabinet using PCL-422 Communicator Remote Mounting Module
- R model includes RS232 serial integration option
- Provides expanded user support (HS2064/ HS2128) and up to 4 ethernet integrations with PowerSeries Neo panels V1.2 and higher
- Refer to [www.dsc.com](http://www.dsc.com) for complete list of integration options

Available in NA, LATAM, Europe, Africa and APAC

Some products are not available in all countries. Please contact your local distributor or refer to [www.dsc.com](http://www.dsc.com) for the most current approval listings.







PGx975 Wireless PowerG Door/Window Contact

- Wafer-thin profile
- Visible link quality indicator on device
- Fully supervised
- Includes double-sided tape
- Large transmission range enabling repeater-free installations
- Easy to install and remove
- Prolonged battery life (5 years with typical use)
- Dimensions: 62 x 25.4 x 7.7mm (2.45 x 1 x 0.3in)
- Available in White or Brown plastic

Available in NA, LATAM, Europe, Africa and APAC



PGx945 Wireless PowerG Door/Window Contact with Auxiliary Input

- Selectable operation of auxiliary input as NO, NC or EOL supervision
- Visible link quality indicator shown on device
- Case and wall tamper
- Ideal for protecting doors, windows and other openings
- Prolonged battery life (8 years with typical use)
- Back tamper switch included on PG4945 and PG8945
- Dimensions: 81 x 32 x 25mm (3.19 x 1.25 x 1in)
- Available in White or Brown plastic

Available in NA, LATAM, Europe, Africa and APAC



PGx904P Wireless PowerG PIR Motion Detector

- Visible link quality indicator on device
- 49 ft (15 m) 90° coverage
- True Motion Recognition™ to distinguish between motion of an intruder and any other disturbances which may cause false alarms
- Pet immunity up to 85 lbs (38 kg)
- Prolonged battery life (6 years with typical use)
- Large transmission range enabling repeater-free installations
- Dimensions: 94.5 x 63.5 x 53mm (3.7 x 63.5 x 2.06in)

Available in NA, LATAM, Europe, Africa and APAC

PGx934P Wireless PowerG PIR Motion Detector with Integrated Camera

- Visual alarm verification day & night
- Full color, high-resolution images transmitted from the premises via Cellular or Ethernet
- CMOS camera with IR illumination
- Auto-setup for brightness and contrast via the control panel
- Front cover and back tamper
- Pet immune up to 85 lbs (38 kg)
- Prolonged battery life (3 years with typical use)
- Dimensions: 125 x 63 x 60mm (4.9 x 2.5 x 2.4in)

Available in NA, LATAM, Europe, Africa and APAC



PGx924 Wireless PowerG Curtain PIR Motion Detector

- Visible link quality indicator on device
- Ideal for protection of doors and windows
- Selectable curtain coverage 6, 12, 18 ft (2, 4, 6 m)
- Front cover and back tamper
- Prolonged battery life (7 years with typical use)

Available in NA, LATAM, Europe, Africa and APAC



PGx984P Wireless PowerG Dual Technology (PIR & MW) Motion Detector

- Visible link quality indicator on device
- Vandal-resistant design
- Dual Technology PIR and K-Band Microwave frequency to reduce false alarms
- Prolonged battery life (5 years with typical use)
- Dimensions: 115 x 60 x 48mm (4.5 x 2.3 x 1.9in)

Available in NA, LATAM, Europe, Africa and APAC







**PGx974P Wireless PowerG Mirror Optic PIR Motion Detector**

- Coverage area – 50 ft (15 m), 90°
- Mirror optics offer exceptionally high detection sensitivity and immunity to false alarms
- Vandal-resistant design (small, recessed and robust slot window)
- Easy to install - no vertical adjustment needed
- Front and back tamper
- Prolonged battery life (7 years with typical use)
- Dimensions: 115 x 60 x 48mm (4.5 x 2.3 x 1.9in)

Available in NA, LATAM, Europe, Africa and APAC



**PGx994 Wireless PowerG Outdoor PIR Motion Detector**

- Visible link quality indicator on device
- Minimizes false alarms while ensuring effective detection of real threats
- Octa-Quad Technology
- Vandal-resistant design
- Black mirror optics for exceptionally high immunity to false alarms
- Prolonged battery life (3 years with typical use)
- Unprecedented, complete anti-masking protection

Available in NA, LATAM, Europe, Africa and APAC



**PGx944 Outdoor PIR Motion Detector with Integrated Camera**

- Innovative Octa-Quad technology to minimize false alarms
- Visual verification with image capture
- Camera range in parallel to PIR coverage - no lost areas
- Robust housing and patented anti-masking protection
- Market-leading black mirror optics
- Built in RF-link status LED
- Remote maintenance with configuration and testing via keypad
- Prolonged battery life (3 years with typical use)

Available in NA, LATAM, Europe, Africa and APAC



**PGx922 Wireless PowerG Glass Break Detector**

- Glass break detection of plate, tempered, laminated and wired glass
- Detection range up to 20 ft (6 m)
- Visible link quality indication shown on the device
- Acoustic Pattern Recognition Technology provides 360° coverage
- Prolonged battery life (5 years with typical use)
- Visible and transmitted low battery indication

Available in NA, LATAM

**PGx938 Wireless PowerG Panic Key**

- Activation via large, easy-to-use button
- Integrated LED to indicate signal transmission and acknowledgment
- Water resistant
- Multifunction clip and neck strap
- Full 2-second delay on panic button
- Fully supervised
- Dimensions: 53 x 33 x 11mm (2.1 x 1.3 x 0.43in)
- Prolonged battery life (7 years with typical use)

Available in NA, LATAM, Europe, Africa and APAC



**PGx949 Wireless PowerG 2-Button Key**

- Activation via 2 large, easy to use buttons
- Integrated LED to indicate signal transmission and acknowledgment
- Built-in buzzer for audible indication
- Water resistant
- Multifunction clip and neck strap
- Full 3-second delay on panic button to reduce false alarms
- Prolonged battery life (7 years with typical use)
- Supplied with a belt clip, a key chain, and a lanyard necklace
- Dimensions: 53 x 33 x 11mm (2.1 x 1.3 x 0.43in)

Available in NA, LATAM, Europe, Africa and APAC



**PGx939 Wireless PowerG 4-Button Key**

- 4 programmable function keys
- Visual and audible indicator to acknowledge requested action
- Full 3-second delay on panic function to reduce false alarms
- Prolonged battery life (8 years with typical use)

Available in NA, LATAM, Europe, Africa and APAC



**PGx929 Wireless PowerG 4-Button Key**

- 4 programmable function keys
- Visual and audible indicator to acknowledge requested action
- Full 3-second delay on panic function to reduce false alarms
- Visible signal quality indication shown on the device
- Prolonged battery life (5 years with typical use)
- Dimensions: 60 x 34.5 x 12.5mm (2.3 x 1.3 x 0.5in)

Available in NA, LATAM, Europe, Africa and APAC





PGx935 Wireless PowerG Shock Detector

- Visible link quality indicator on the device
- High immunity to background vibrations
- Adjustable shock/vibration thresholds
- Front and back tamper
- Optional magnetic reed switch contact
- Early detection of forceful attacks or low-level shocks
- Protects windows, doors, walls and roofs against forced entry
- Quick and easy installation using unique 7-segment shock meter and push buttons
- Prolonged battery life (5 years with typical use) with all sensors enabled

Available in NA, LATAM, Europe, Africa and APAC



PGx926 Wireless PowerG Smoke Detector

- Photoelectric smoke detector
- Provides alerts for smoke, tamper and device low battery
- Visible link quality indication shown on the device
- Fully supervised
- Maintenance and battery condition indication
- Built in 85db alarm buzzer
- Prolonged battery life (8 years with typical use)

Available in NA, LATAM, Europe, Africa and APAC



PGx916 Wireless PowerG Smoke and Heat Detector

- Photoelectric smoke detector with built-in heat sensor
- Provides alerts for smoke, tamper and device low battery
- Visible link quality indication shown on the device
- Fully supervised
- Maintenance and battery condition indication
- Built in 85db alarm buzzer
- Certified by the most strict and demanding international standards
- Prolonged battery life (8 years with typical use)

Available in NA, LATAM, Europe, Africa and APAC

PGx913 Wireless PowerG CO Detector

- Early warning of carbon monoxide (CO) poisoning danger
- Visual and audible alarm indications upon CO detection
- Built-in 95db alarm buzzer and large flashing LED alarm
- Visible and transmitted low battery indication
- Fully certified by the most strict and demanding international standards for safety products in Europe (LPCB UK, EN 50291) and USA (UL 2075)
- Auto-test and manual test buttons included
- Long battery life (4 years with typical use)

Available in US, LATAM, Europe, Africa and APAC



PGx905 Wireless PowerG Temperature Detector

- Visible link quality indication shown on the device
- Programmable temperature warning and alarm thresholds
- Optional probe to monitor refrigerator, freezer and outdoor temperatures
- Front and back tamper protected
- Prolonged battery life (7 years with typical use)
- Dimensions: 81 x 32 x 25mm (3.19 x 1.25 x 1in)
- External temperature probe PGTEMP-PROBE

Available in NA, LATAM, Europe, Africa and APAC



PGx985 Wireless PowerG Flood Detector

- Visible signal quality shown on the device
- Fully supervised
- 6 ft (2 m) wire water probe
- Visible and transmitted low battery indication
- Prolonged battery life (8 years with typical use)
- Dimensions: 81 x 34 x 25mm (3.19 x 1.25 x 1in)

Available in NA, LATAM, Europe, Africa and APAC







PGx901 Wireless PowerG Indoor Siren

- Visible link quality indicator on device
- 110db siren with strobe light
- Differentiated audible alerts for intrusion and fire
- Prolonged battery life (8 years with typical use)
- Dimensions: 161 x 161 x 50mm (6.44 x 6.44 x 1.75in)

Available in NA, LATAM, Europe, Africa and APAC



PGx911 Wireless PowerG Outdoor Siren

- 110db siren output
- Strobe light functionality for visual indication
- Sleek design and robust weatherproof housing (IP55)
- Fully supervised
- Prolonged battery life (8 years with typical use)
- Differentiated alarm sounds for intrusion, fire, gas and flood
- Large print screen area for customizable logos
- Dimensions: 295 x 186 x 63mm (11.63 x 7.31 x 2.5in)
- Available with Amber strobe, depending on country

Available in NA, LATAM, Europe, Africa and APAC



PGx920 Wireless PowerG Repeater

- Extends the overall wireless range
- LED indications for power failure, activity and installation performance diagnostics
- Compact and easy to install
- Front and back tamper protected
- Replacement Battery BATT1.3-4.8V
- Mains powered with 48 hour backup battery (rechargeable)
- Dimensions: 161 x 161 x 50mm (6.44 x 6.445 x 1.74in)

Available in NA, LATAM, Europe, Africa and APAC

Intrusion Detectors



 WS4904P Wireless Pet-Immune PIR Detector	 WS4945 Wireless Door/Window Contact	 EV-DW4927SS Wireless Shock Sensor with Built-In Door/Window Contact	 EV-DW4975 / EV-DW8975 Wireless Vanishing Contact	 EV-DW4917 Wireless Recessed Door Transmitter	 AC-100 / AC-500 Wired Glassbreak Detector	 BV-500 Wired 360° Ceiling-Mount PIR Motion Detector
 LC-100-PI Wired PIR Detector with Pet-Immunity	 BV-300 Wired PIR Detector	 LC-151/171 Wired Pet-Immune Dual-Tech Outdoor Motion Detectors	 SS-102 Wired Shock Sensor	 BV-600 Wired Dual-Element, Pet-Immune PIR Motion Detector	 LC-103-PIMSK / LC-104-PIMW Wired Dual-Tech Motion Detector with Pet-Immunity	 AMB-500 Addressable Ceiling-Mount PIR Detector
 AMB-300 Addressable PIR Detector	 AMB-600 Addressable Pet-Immune PIR Detector	 AMP-700 / AMP-701 AMP-702 / AMP-704 Addressable Contact Modules				




Safety Sensors

 WS4936 Wireless Photoelectric Smoke Detector	 WS4913 Wireless Carbon Monoxide Detector	 WS4985 Wireless Flood Detector	 FSA-210/410 Wired Photoelectric Smoke Detector	 FSB-210 Series Addressable Photoelectric Smoke Detector
---	---	---------------------------------------	---	--

Control Panels

 PC1864 8-64 Zone Control Panel	 PC1832 8-32 Zone Control Panel	 PC1616 6-16 Zone Control Panel
---------------------------------------	---------------------------------------	---------------------------------------



Keypads, Arming Devices & Panic Buttons

 PK5500 64-Zone LCD Full-Message Keypad	 PK5501 64-Zone LCD Picture Icon Keypad	 PK5508 8-Zone LED Keypad	 PK5516 16-Zone LED Keypad	 PTK5507W TouchScreen Security Interface	 PTK5507S TouchScreen Security Interface	 WT5500-WT5500P 2-Way Wire Free Keypad (optional Proximity tag support)	 WTK5504 / WTK5504P Wireless TouchScreen Arming Station
 WS4949 2-Button Wireless Key	 WS4959 5-Button Wireless Key	 WT4989 2-Way Wireless Key	 WS4938 1-Button Wireless Personal Panic	 WS4939 4-Button Wireless Key	 RFK5500 64-Zone LCD Full-Message Keypad with Built-In Wireless Receiver, 32 wireless zones	 RFK5564 64-Zone Full-Message Keypad with Built-In Wireless Receiver (up to 64 wireless zones)	 RFK5501 64-Zone LCD Picture Icon Keypad with Built-In Wireless Receiver, 32 wireless zones



Repeaters, Recievers, Modules and Communicators

 WS4920 Wireless Repeater	 RF5132-433 Wireless Receiver	 PC5320 Multiple Wireless Receiver Module	 TR5164-433 2-Way Wireless Transceiver	 PC5108 8-Zone Hardware Expander	 PC5100 Addressable Zone Expander	 IT-230 RS-422 Interface Module	 IT-100 Serial Integration Module
 PC5200 / PC5204 Power Supply Modules	 PC5208 Programmable Output Module	 3G2060R HSPA Cellular Alarm Communicator	 TL260R Internet Alarm Communicator	 TL2603GR Internet & HSPA Dual-Path Alarm Communicator			



PC1616 PowerSeries Control Panel

- 6 on-board zones
  - Expandable up to 32 zones in any combination of wireless or hardwired zones
  - 2 PGM outputs: expandable to 14 (PC5204, PC5208)
  - Connect up to 8 supervised keypads
  - Supports wire free keypads with TR5164-433 transceiver
- Template programming
  - 2 partitions
  - 500-event buffer
  - 48 user codes
  - CP-01 compliant
  - Compatible with leading edge interactive services supported by DSC

Available in NA, LATAM, EMEA and APAC



PC1832 PowerSeries Control Panel

- 8 on-board zones
  - Expandable up to 32 zones in any combination of wireless or hardwired zones
  - 2 PGM outputs: expandable to 14 (PC5204, PC5208)
  - Connect up to 8 supervised keypads
  - Template programming
  - 4 partitions
- 500-event buffer
  - 72 user codes
  - CP-01 compliant
  - Supports wire free keypads with TR5164-433 transceiver
  - Compatible with leading edge interactive services supported by DSC

Available in NA, LATAM, EMEA and APAC



PC1864 PowerSeries Control Panel

- 8 on-board zones
  - Expandable up to 64 wireless zones in any combination of wireless or hardwired zones
  - 4 PGM outputs: expandable to 14 (PC5204, PC5208)
  - Template programming
  - Connect up to 8 supervised keypads
  - 8 partitions
- 500-event buffer
  - 95 user codes
  - CP-01 compliant
  - Supports wire free keypads with TR5164-433 transceiver
  - Compatible with leading edge interactive services supported by DSC

Available in NA, LATAM, EMEA and APAC

Control Panels Overview | PowerSeries Panels Features

Features	PC1616	PC1832	PC1864
Number Of On-Board Zones	6	8	8
Total Zones Supported	32	32	64
Keypad Zone Expansion	Yes	Yes	Yes
Hardwired Zone Expansion	Yes	Yes	Yes
Hardwired Zones	16 (1 x PC5108)	32 (3 x PC5108)	64 (7 x PC5108)
Wireless Zone Expansion	Yes	Yes	Yes (64 Wireless)
Addressable Zone Expansion	Yes	Yes	Yes
Number of Keypads	8	8	8
Number of Wireless Receivers	4 (PC5320)	4 (PC5320)	4 (PC5320)
On-Board PGM Outputs	PGM 1 = 50 mA PGM 2 = 300 mA	PGM 1 = 50 mA PGM 2 = 300 mA	PGM 1, 3, 4 = 50 mA PGM 2 = 300 mA
Number of Main Panel Low-Current PGM Outputs	1	1	3
Number of Main Panel High-Current PGM Outputs	1	1	1
PGM Expansion	8 x 50 mA (PC5208) 4 x 500 mA (PC5204)	8 x 50 mA (PC5208) 4 x 500 mA (PC5204)	8 x 50 mA (PC5208) 4 x 500 mA (PC5204)
Number of Additional Low-Current PGM Outputs	8	8	8
Number of Additional High-Current PGM Outputs	4	4	4
Number of Access Codes	47+ Master Code	71+ Master Code	94+ Master Code
Number of Partitions	2	4	8
Panel Event Buffer	500	500	500
Phone Line Supervision	Yes	Yes	Yes
Siren Supervision	Yes	Yes	Yes
Bell Output	12 V / 700 mA (cont)	12 V / 700 mA (cont)	12 V / 700 mA (cont)
SIA CP-01 Compliant	Yes	Yes	Yes
Event-Initiated Personal Paging	Yes	Yes	Yes
Upload/Download Support	Yes	Yes	Yes
Direct-Connect (PC Link) Downloading Support	Yes	Yes	Yes
DLS SA End-User Downloading Support	yes (v4.1 & higher)	yes (v4.1 & higher)	yes (v4.1 & higher)
Internet Alarm Communications	Yes	Yes	Yes
Audio Alarm Verification	Yes	Yes	Yes
Cellular Alarm Communications	Yes	Yes	Yes
Battery Required	4 Ah / 7 Ah / 14 Ahr	4 Ah / 7 Ah / 14 Ahr	4 Ah / 7 Ah / 14 Ahr
Interactive	Yes (v4.6)	Yes (v4.6)	Yes (v4.6)





**PK5500 PowerSeries 64-Zone LCD Full-Message Keypad  
RFK5500 with Built-In Wireless Receiver  
RFK5564 with Built-In Wireless Receiver**

- Multi-language support
- Global partition status
- Full 32-character programmable labels
- Modern, slim-line landscape keypad
- Enlarged keypad buttons
- 5 programmable function keys
- Input/Output terminal can be programmed to operate as a zone input, programmable output or as a low temperature sensor
- 3 one-touch emergency keys
- Multiple door chime per zone
- Adjustable backlight and keypad buzzer
- Wire channel
- Dual wall-mount and front cover tamper
- Easy-to-install mounting hinge
- Surface or single-gang box mount
- AC status ICON
- RFK5500 and RFK5500-868 includes all of the same features and supports 32 wireless zones and 16 wireless keys
- RFK5564 includes all of the same features and supports 64 wireless zones and 16 wireless keys

Available in NA, LATAM, EMEA and APAC



**PK5501 PowerSeries 64-Zone LCD Picture Icon Keypad  
RFK5501 with Built-In Wireless Receiver**

- Modern, slim-line landscape keypad
- Enlarged keypad buttons
- 5 programmable function keys
- Input/Output terminal can be programmed to operate as a zone input, programmable output or as a low temperature sensor
- 3 one-touch emergency keys
- Multiple door chime per zone
- Adjustable backlight and keypad buzzer
- Wire channel
- Dual wall-mount and front cover tamper
- Easy-to-install mounting hinge
- Surface or single-gang box mount
- AC status ICON
- Available with English function keys
- RFK5501 includes all of the same features and supports 32 wireless zones and 16 wireless keys

Available in NA, LATAM, EMEA and APAC

**PK5508 PowerSeries 8-Zone LED Keypad  
RFK5508 with Built-In Wireless Receiver**

- Modern, slim-line landscape keypad
- Enlarged keypad buttons
- 5 programmable function keys
- Input/Output terminal can be programmed to operate as a zone input, programmable output or as a low temperature sensor
- 3 one-touch emergency keys
- Multiple door chimes per zone
- Adjustable backlight and keypad buzzer
- Wire channel
- Dual wall-mount and front cover tamper
- Easy-to-install mounting hinge
- Surface or single-gang box mount
- AC status ICON
- RFK5508 includes all of the same features and supports 32 wireless zones and 16 wireless keys

Available in NA, LATAM, EMEA and APAC



**PK5516 PowerSeries 16-Zone LED Keypad  
RFK5516 with Built-In Wireless Receiver**

- Modern, slim-line landscape keypad
- Enlarged keypad buttons
- 5 programmable function keys
- Input/Output terminal can be programmed to operate as a zone input, programmable output or as a low temperature sensor
- 3 one-touch emergency keys
- Multiple door chimes per zone
- Adjustable backlight and keypad buzzer
- Wire channel
- Dual wall-mount and front cover tamper
- Easy-to-install mounting hinge
- Surface or single-gang box mount
- AC status ICON
- RFK5516 includes all of the same features and supports 32 wireless zones and 16 wireless keys

Available in NA, LATAM, EMEA and APAC



**PTK5507 PowerSeries TouchScreen Security Interface**

- 7" full color display
- Slim modern design (800x480 resolution)
- Intuitive LED indication of security system status
- Picture frame feature
- Clock feature
- Output control
- Intuitive user interface
- Customizable home screen and wallpaper
- Menu user programming
- Installer programming
- Virtual keypad
- SD card is not included
- Compatible with PC1864, PC1832, P C1616 control panels
- Multi-language support

Available in NA, LATAM, EMEA and APAC





WT5500 2-Way Wire Free Keypad

- 2x16 full message display
- Intuitive clock programming
- Multiple door chime
- Ambient light sensor
- Display and keymat backlighting
- Outdoor temperature display
- Wall and Deskstand\* mount
- Proximity Tag PT4 Arm/Disarm (WT5500P Only)
- Installer's programming
- Multi-language support
- 5 programmable function keys
- 3 one-touch emergency keys
- Tamper switch
- Nominal battery life – 1 year
- Compatible with IMPASSA and PowerSeries (via TR5164-433)
- Visual armed status during sleep mode
- Blue LCD display screen
- Supports Alarm.com messaging
- Available in 433 MHz and 868 MHz

Available in NA, LATAM and APAC  
\* WT5500D or WT5500DMK



WTK5504 2-Way Wireless TouchScreen Arming Station

- 4.3" full color display
- AC plug-in
- Rechargeable batteries
- 24 hr battery back-up user programming user function
- Night light sleep mode
- Proximity arm/disarm (WTK5504P only)
- Voice chime/voice prompts
- Wall and desk stand mount
- Multi-language support
- 3-5 year battery life
- Tamper switch
- Compatible with IMPASSA and PowerSeries (via TR5164-433)
- 5 programmable function keys
- 3 emergency keys
- Supports Alarm.com messaging

Available in NA, LATAM and APAC

Keypad Overview | PowerSeries Keypad Features

General Features	PK5500*	PK5501*	PK5516*	PK5508*
Display Type	LCD/ALPHA	LCD/FIXED	LED	LED
Zone Support	64	64	16	8
Partition Support	8	8	8	8
Number of Function Keys	5	5	5	5
Dedicated Function Keys	Yes	Yes	Yes	Yes
Dedicated Emergency Keys	Yes	Yes	Yes	Yes
Dual Emergency Keys	No	No	No	No
Key Size	Large	Large	Large	Large
AC Status LED	Yes	Yes	Yes	Yes
Integrated Low Temperature Sensor	Yes	Yes	Yes	Yes
Zone Input	Yes	Yes	Yes	Yes
PGM Output	Yes	Yes	Yes	Yes
DEOL Zone Supervision	Yes	Yes	Yes	Yes
Intuitive Clock Programming	Yes	No	No	No
Backlighting Adjustment Control	Yes	Yes	Yes	Yes
Buzzer Adjustment Control	Yes	Yes	Yes	Yes
Multiple Chimes Per Zone	Yes	Yes	Yes	Yes
Hardware				
Bezel Color	White	White	White	White
Soft/Hard Lens	Hard	Hard	Hard	Hard
Profile	Landscape	Landscape	Landscape	Landscape
* Integrated RF Receiver Models	RFK5500/RFK5564	RFK5501	RFK5516	RFK5508
Buzzer/Backlighting Adjustment Retained After Power Loss	Yes	Yes	Yes	Yes
“Hands Free” Installation Hinge	Yes	Yes	Yes	Yes
Wire Channel	Yes	Yes	Yes	Yes
Single-Gang Box Mount	Yes	Yes	Yes	Yes
Double-Gang Box Mount	Yes	Yes	Yes	Yes
Case Tamper (Dual Tamper Support)	Yes	Yes	Yes	Yes

\* RFK versions of these keypads are available with a built-in wireless receiver and support 32 or 64 wireless zones and 16 wireless keys





PC5320 Multiple Wireless Receiver Module

- Multi-frequency support for combination of 900/433 MHz receivers
- Compatible with PC1616, PC1832 and PC1864 PowerSeries control panels
- Can be used to connect up to 4 wireless receivers for increased coverage


Available in NA, LATAM, EMEA and APAC



PC5100 PowerSeries Addressable Zone Expander

- Connect up to 32 addressable detectors (AML)
- Detectors can be home-run, t-tapped or daisy chained
- Easy detector enrollment process
- Compatible with PC1616, PC1832 and PC1864 control panels


Available in NA, LATAM, EMEA and APAC



PC5108 PowerSeries 8-Hardwire Zone Expander

- Adds 8 hardwire zones
- AUX power, 125 mA (PTC protected)
- Compatible with PC1616, PC1832 and PC1864 control panels

Available in NA, LATAM, EMEA and APAC



PC5200 / PC5204 PowerSeries Power Supply Modules

- Fully supervised for AC failure, low battery and AUX failure
- PC5204 adds 4 programmable high current voltage outputs: rated at 1 Amp @ 12 VDC, output #1 can be used as a supervised bell output
- Connect one PC5204 and up to four PC5200 supervised modules on a system
- Provides up to 1 Amp @ 12 VDC
- Compatible with PC1404, PC1616, PC1832 and PC1864 control panels

Available in NA, LATAM, EMEA and APAC



PC5208 PowerSeries Programmable Output Module

- Provides 8 low current (50 mA) PGM voltage outputs
- Compatible with PC1616, PC1832 and PC1864 control panels

Available in NA, LATAM, EMEA and APAC

PC5400 Printer Interface Module

- Compatible with PC1616, PC1832 and PC1864 control panels
- Can be used to support a serial printer

Available in NA, LATAM, EMEA and APAC



PC5950 Universal 2-Way Vox Audio Verification Module

- Supports both 2-way audio VOX and push-to-talk verification
- Supports 4 microphones and 2 speakers
- KEYBUS direct connect allows all programming to be performed at the system keypad or remotely using dls 5 software
- KEYBUS compatible with PC1616, PC1832 and PC1864 control panels
- Universal installation compatibility with any control panel using either PGM and/or Bell dry contact outputs
- Silent/Listen-in functionality on hold-up alarms (activates only when an alarm occurs)
- User call-in feature

Available in NA, LATAM, EMEA and APAC



IT-230 RS-422 Interface Module

- Compatible with PowerSeries panels v4.5 and higher
- 4-wire keybus and included PC-LINK header hookup
- Compatible with leading-edge interactive solutions supported by DSC


Available in NA



IT-100 PowerSeries Integration Module

- Bi-directional RS-232 interface
- Real-time zone status
- Fully programmable
- 4-wire hook-up to KEYBUS
- Virtual keypad mode
- Compatible with PowerSeries control panels PC1616/PC1832/PC1864
- Thermostat control functionality via a DSC Escort module

Available in NA, LATAM, EMEA and APAC





PC5962 Contoured Audio Station

- Equipped with speaker/microphone
- New modern look
- Fits seamlessly to side of PK/RFK series of keypads
- Specifically designed for 2-way voice verification
- 4-wire connection to module
- Compatible with PC5950 module

Available in NA, LATAM, EMEA and APAC



PC5964E Large Speaker Station

- Equipped with speaker/microphone
- New modern look
- Specifically designed for 2-way voice verification
- Bell follower functionality (replaces internal sounder on premises) (PC5950 only)
- 4-wire connection to module
- Surface or single-gang box mount
- Compatible with PC5950 and HSM2955(R) modules

Available in NA, LATAM, EMEA and APAC



PC5961E Stand-Alone Audio Station

- Equipped with speaker/microphone
- New modern look
- Specifically designed for 2-way voice verification
- 4-wire connection to module
- Surface or single-gang box mount
- Compatible with PC5950 and HSM2955(R) modules

Available in NA, LATAM, EMEA and APAC



RF5132-433 / RF5132-868 PowerSeries Wireless Receiver

- Supports 32 wireless zones, 16 wireless keys
- All wireless detectors are fully supervised for communication integrity
- Compatible with PC1616, PC1832 and PC1864 control panel
- RF5132-433 is compatible with PC585, PC1616, PC1832 and PC1864 control panels
- Available in either 433 MHz or 868 MHz

Available in NA, LATAM, EMEA and APAC



TR5164-433 PowerSeries 2-Way Wireless Transceiver

- Supports both 2-way and 1-way wireless devices
- Supports 4 wire-free keypads (WT5500 /WTK5504)
- Supports 16 wireless keys (any combination of 1-way or 2-way wireless keys)
- Supports 60 wireless zones on PC1864
- 8-partition support for 1-way wireless keys
- Compatible with PC1616, PC1832 and PC1864 v4.6+

Available in NA, LATAM and APAC

3G2060(R) HSPA Cellular Alarm Communicator

- Compatible with PC1864/1832/1616 control panels (v4.1 and higher)
- Back up and primary HSPA alarm communication
- Panel remote uploading/downloading support via cellular
- Supervision heartbeats via cellular
- 128-bit AES encryption via cellular
- Full event reporting
- SIA or Contact ID protocol (with PowerSeries V4.5+ and communicator V1.1+)
- Compatible with Sur-Gard System I-IP/II/III/IV/5 monitoring station receivers
- UL standard & encrypted line security
- ULC passive or active line security levels
- Antenna Extension Kits available: GS-15ANTQ, GS-25ANTQ, GS-50ANTQ
- Signal strength and trouble display
- PC-Link connection

Available in NA, LATAM, APAC, Europe, Africa



TL2603G(R) Internet and HSPA Dual-Path Alarm Communicator

- Compatible with PC1864/1832/1616 control panels (v4.1 and higher)
- Fully redundant Internet and HSPA dual-path alarm communication
- Integrated call routing
- Panel remote uploading/downloading support via cellular and Internet
- Supervision heartbeats via cellular and Internet
- 128-bit AES encryption via cellular and Internet
- Full event reporting
- SIA or Contact ID protocol (with PowerSeries V4.5+ and communicator V1.1+)
- Compatible with Sur-Gard System I-IP/II/III/IV/5 monitoring station receivers
- UL standard & encrypted line security
- ULC passive or active line security levels
- Active cellular account is required to use IP function
- Antenna Extension Kits available: GS-15ANTQ, GS-25ANTQ, GS-50ANTQ
- Signal strength and trouble display
- PC-Link connection

Available in NA, LATAM, APAC, Europe, Africa



TL260(R) Internet Alarm Communicator

- Compatible with PC1864/PC1832/PC1616 control panels (v4.1 and higher)
- Panel remote uploading & downloading via internet using DLS 5
- Programmable using DLS 5 or keypad
- Supervision heartbeat via internet
- 128 Bit AES Encryption
- Full event format
- SIA or Contact ID protocol (with PowerSeries V4.5+ and communicator V1.1+)
- Compatible with Sur-Gard System I-IP/II/III/IV/5 monitoring station receivers

Available in NA, LATAM, APAC, Europe, Africa







PC4020 MAXSYS Control Panel

- 16 on-board zones
- Expandable up to 128 zones using hardwire, wireless modules and addressable zones
- Supports up to 16 hardwired keypads
- 8 partitions
- Expandable to 64 wireless zones
- 1,500 user codes (4 or 6 digit)
- 3,000 event buffer
- 9 account and 3 phone numbers
- Built-in telephone line and siren supervision
- Automatic SIA and Contact ID formats
- Supports Cellular and T-Link™ alarm communicators
- Full upload/download support with DLS 2002 software
- COMBUS hardwired expansion

Available in NA, LATAM, EMEA and APAC



MaxKit MAXSYS Access Control Kit

This affordable package is the perfect access control starter kit. It has all the essentials you need: control panel, access control module, reader and keys in one low-cost package. If needed, the system can be easily expanded

Includes:

- 1 PC4020 control panel
- 1 PC4820 2-reader access control module
- 1 P225W26 ioProx reader
- 10 P40KEY ioProx dual-encoded proximity keys

Available in NA, LATAM and APAC



LCD4501 MAXSYS Programmable-Message LCD Keypad

- Connect up to 16 keypads
- Large, backlit, 2-line, 32-character display
- Plain-language display of zone status, system status, trouble conditions, event buffer, system instructions, date and time
- Ready, Armed and Trouble LEDs
- 5 programmable function keys
- 4 keypad-activated alarms: Panic, Auxiliary, Fire and Duress
- Backlight boost

Available in NA, LATAM, EMEA and APAC

PC4204 / PC4204CX MAXSYS Power Supply/Relay Output/Combus Repeater Module

- Connect up to 16 modules
- 4 programmable form 'C' relays rated at 2 Amps @ 30 VDC
- Fully supervised for AC failure, low battery and AUX failure


Available in NA, LATAM, EMEA and APAC



PC4216 MAXSYS 16 Low Current Output Module

- Provides 16 programmable outputs:rated at 50 mA @ 12 VDC
- Connect up to 9 PC4216 modules per system


Available in NA, LATAM, EMEA and APAC



PC4401 MAXSYS Data Interface Module

- Connect up to 4 modules
- Capable of performing as either a bi-directional RS-232 interface, PC-Link isolator or printer module
- Real-time zone status
- Fully programmable
- 4-wire hook-up to COMBUS


Available in NA, LATAM, EMEA and APAC



PC4820 MAXSYS 2-Reader Access Control Module

- Connect up to 16 modules
- Multiple reader technologies
- 2 supervised lock outputs: 250 mA per output
- 2 access door support per module for up to total of 32 on system
- 99 date schedules
- 4 holiday groups
- Arm/Disarm partitions via access control
- PC5003C beige cabinet included
- 64 user access levels

Available in NA, LATAM, EMEA and APAC






RF4164-433 MAXSYS Wireless Receiver

- Supports 64 wireless zones, 16 wireless keys
- Up to 8 receivers on one system
- All wireless detectors are fully supervised for communication integrity

Available in NA, LATAM, EMEA and APAC



PC4108A / PC4116 MAXSYS 8/16 Hardwire Zone Expanders

- PC4108A adds 8 hardwire zones
- PC4116 adds 16 hardwire zones
- AUX power rated at 250 mA (PTC protected)

Available in NA, LATAM, EMEA and APAC



PC4632 / PC4664 MAXSYS 32/64 Point Graphic Annunciators

- Egg-crate backplate for flexible LED locations
- Pre-printed point display transparency
- Clear transparencies (2) for custom graphics

Available in NA, LATAM, EMEA and APAC



TL250 Internet Alarm Communicator

- Compatible with PowerSeries (v3.24 and higher) and MAXSYS (v3.31 and higher) control panels
- Works over local LAN/WAN network or the Internet
- 128-bit AES encryption (NIST approved)
- Supports DHCP (dynamic IP addresses)
- Low network bandwidth requirements
- Compatible with 10/100BaseT networks
- Reports events to 2 different receiver IP addresses
- Polling and hardware substitution protection
- Instant, always-on IP communication
- Software upgrades via network
- 4 on-board programmable inputs and 2 programmable voltage outputs as stand-alone module
- Programmable through the system keypad, PK5500 LCD keypad or T-Link Console software
- Download control panel via Internet with DLS software
- Compatible with Sur-Gard System I-IP/II/ III/IV/5 monitoring station receivers
- UL standard & encrypted line security
- ULC passive or active line security levels A1-A4

Available in NA, LATAM, EMEA and APAC

T-REX Request-To-Exit Detector

MAXSYS supports passive infrared request-to-exit detector with patented X-Y targeting™ and DSP (Digital Signal Processing).

To order or request more information on Kantech products, please visit [www.kantech.com](http://www.kantech.com).

Available in NA, LATAM, EMEA and APAC



Readers

MAXSYS supports a wide range of 26-bit Weigand readers: Polaris™, ioProx™, Shadowprox™, HID and Kantech XSF Technologies.

To order or request more information on Kantech products, please visit [www.kantech.com](http://www.kantech.com).

Available in NA, LATAM, EMEA and APAC







# Wireless Solutions

Security

### Intrusion Detectors

Pet Immune Detector  
up to 60lb (27 kg)  
WS4904P

Shock Sensor  
EV-DW4927

Tri-Zone Door/Window Contact  
WS4965

Vanishing Door/Window Contact  
EV-DW4975

Door/Window Contact  
WS4945

Recessed Door Transmitter  
EV-DW4917

Safety

### Safety Sensors

Wireless Photoelectric  
Smoke Detector  
WS4936

Carbon Monoxide Detector  
WS4913

Flood Detector  
WS4985

Remote Control

### Keypads, Arming Devices & Panic Buttons

2-Way Wireless TouchScreen  
Arming Station  
WTK5504

Wire-Free Keypad  
WT5500

5 Button Key  
WT4989

4 Button Key  
WS4939

2 Button Key  
WS4949

5 Button  
12 Channel Key  
WS4959

1-Button  
Personal Panic  
WS4938

Siren & Repeaters

### Sirens & Repeaters

2-Way Wireless  
Outdoor Siren  
WT4901

2-Way Wireless  
Indoor Siren  
WT4911

Wireless  
Repeater  
WS4920

### Control Panels

DSC Touch -  
7 inch 'All-in-One'  
TouchScreen  
SCW9067

IMPASSA  
2-Way Wireless  
Security System  
SCW9055/9057



SCW9067 Touch - 7 inch ‘All-in-One’ TouchScreen

- 7 inch TouchScreen with a resolution of 800x480
- Built in apps such as Contact info and Photo Frame
- Built in Camera, takes photos on Disarm and Alarm events
- Compatible with DSC 433 Mhz One-Way Wireless products
- Dual-Path Connectivity with Integrated Wi-Fi and Cellular
- Z-Wave, Bluetooth, Image Sensor and Cellular radios built in to work with smart home products
- Integrated with Alarm.com to offer Interactive Services through iOS and Android apps
- Software updates over Wi-Fi and manually with an SD card
- Supports 59 Wireless zones and 242 User codes
- Built in Two-way Voice over Cellular
- Built in Siren

Available in NA and AUS



SCW9055 / SCW9057 IMPASSA Self-Contained Wireless Security System

- Supports 64 wireless zones and 16 wireless keys (without using a zone slot)
- Optional integrated HSPA (3G) cellular, internet or dual communicator
- Cellular signal strength read-out to optimize placement
- Built-in 2-way audio VOX and push-to-talk alarm communication via phone line and cellular \*
- 2-way audio is available only on IMPASSA 9057 Self-Contained Wireless Security Systemt
  - 4 keypad support
  - 4 siren support
  - 16 wireless keys
- Easy wireless device enrollment process
- Template programming
- Full 32-character programmable labels
- 5 programmable function keys
- Individual FAP Emergency keys
- 17 user access codes
- 500 event buffer
- False alarm reduction features (CP-01)
- Enlarged keypad buttons
- Outdoor temperature display (requires wireless siren)
- Label library
- Compatible with leading edge interactive services (supported by DSC SCW9057 model only)

Available in NA, LATAM, EMEA and APAC

\*2-way is available only on SCW9057

WTK5504 2-Way Wireless TouchScreen Arming Station

- 4.3" full color display
- AC plug-in
- Rechargeable batteries
- 24 hr battery back-up user programming user function
- Night light sleep mode
- Proximity arm/disarm (WTK5504P only)
- Voice chime/voice prompts
- Wall and desk stand mount
- Multi-language support
- 3-5 year battery life
- Tamper switch
- Compatible with IMPASSA, Alexor and PowerSeries (via TR5164-433)
- 5 programmable function keys
- 3 emergency keys
- Supports Alarm.com messaging

Available in NA, LATAM and APAC



WT5500 2-Way Wire Free Keypad

- 2x16 full message display
- Intuitive clock programming
- Multiple door chime
- Ambient light sensor
- Display and keymat backlighting
- Outdoor temperature display
- Wall and Deskstand\* mount
- Proximity Tag PT4 Arm/Disarm (WT5500P Only)
- Installer's programming
- Multi-language support
- 5 programmable function keys
- 3 one-touch emergency keys
- Tamper switch
- Nominal battery life – 1 year
- Compatible with IMPASSA and PowerSeries (via TR5164-433)
- Visual armed status during sleep mode
- Blue LCD display screen
- Supports Alarm.com messaging
- Available in 433 MHz or 868 MHz

Available in NA, LATAM, EMEA and APAC

\* WT5500D or WT5500DMK








3G2055 HSPA Cellular Alarm Communicator

- Compatible with IMPASSA Wireless Panel
- Back up and primary HSPA alarm communication
- Panel remote uploading/downloading support via cellular
- Supervision heartbeats via cellular
- 128-bit AES encryption via cellular
- SIA and Contact ID protocol
- Signal strength and trouble display via IMPASSA keypad
- Full event reporting
- Compatible with Sur-Gard System I-IP/II/III/IV/5 monitoring station receivers
- Command and Control via SMS
- 2-Way voice over cellular (with IMPASSA v1.1 firmware)
- Antenna Extension Kits available: GS-8ANTP, GS-15ANTQ, GS-25ANTQ, GS-50ANTQ

Available in NA, LATAM and EMEA



3G8055(I) / CD8055(I) - IMPASSA HSPA / CDMA Cellular Alarm Communicator

- Compatible with IMPASSA v1.3+
- 4 integrated communicator models: 3G8055; 3G8055I\*; CD8055\*\*; CD8055I\*/\*\*
- 2 integrated cellular technologies: HSPA (3G); CDMA (only available in US)
- Cellular signal strength read-out to optimize placement
- Built-in Z-Wave automation
- Easy wireless device enrollment process
- Supports image sensors via virtual zones\*\*\*
- Alarm.com AirFX Support
- Remote firmware upgradable over cellular
- Allows compatible web services
- Internal antennae

Available in NA, LATAM and APAC

\* Required for supporting image sensors

\*\* Only available in US

\*\*\* Only the (I) model



WS4945\* / WS8945 Wireless Door/Window Contact

- Built-in reed switch
- Normally closed external contact input
- 1 lithium battery included
- Reliable 433 MHz or 868 MHz technology
- Available in white or brown housing
- Case and wall tamper

Available in NA, LATAM, EMEA and APAC

\* WS4945N normally open version available



EV-DW4975 / EV-DW8975 Vanishing Contact

- Built-in reed switch
- Wafer-thin profile
- Long-life lithium battery included
- 5/8" (16 mm) magnet gap
- Reliable 433 MHz or 868 MHz technology
- Includes double-sided tape

Available in NA, LATAM and APAC



EV-DW4917 Wireless Recessed Door Transmitter

- Small, compact design
- Long-life lithium battery included
- Flexible mounting options (screw mount or press fit)
- Reliable 433 MHz technology
- Powerful, rare earth magnet
- Ships complete with flanged/non-flanged, brown/white access caps

Available in NA, LATAM and APAC



WS4965 Tri-Zone Wireless Door/Window Contact

- 3 zones in 1 (each zone has an individual serial number)
- 1 reed/magnet combination zone
- Tilt switch mode for overhead doors
- 2 normally closed external contact inputs
- Long-life lithium battery included
- 1/2" (13 mm) maximum magnet gap
- Low-battery LED indicator
- Case tamper
- Reliable 433 MHz technology
- Includes backplate

Available in NA, LATAM and APAC



**WS4904 / WS8904 Wireless Passive Infrared Detector**  
**WS4904P Wireless Pet-Immune Passive Infrared Detector**

- Based on the Bravo® 3D hardwire motion detector
- High-traffic shutdown
- WS4904P features pet immunity up to 60 lb (27 kg)
- Fast and Slow detection settings for easy adjustment
- 1 lithium battery included
- Reliable 433MHz or 868 MHz technology
- 40ft detection range

Available in NA, LATAM, EMEA and APAC

\* WS4904P offers enhanced wireless communication in areas with high RF noise



**EV-DW4927SS Wireless Shock Sensor With Built-In Door/Window Contact**

- Electro mechanical shock sensor
- Adjustable sensitivity
- Alarm pre-alert
- Built-in reed switch contact
- User-replaceable lithium battery
- 433MHz

Available in NA, LATAM and APAC



**WT4989 / WT8989 2-Way Wireless Key**

- Backlit ICON display
- Built-in buzzer for audible feedback
- Key tactile feedback
- 4 one touch function keys, programmable for up to 6 functions
- Status button indication
- Key-lock function to prevent accidental button presses
- Active alarm indication
- Water resistant
- Multifunction clip
- Nominal Battery life – 3 years
- Compatible with IMPASSA and PowerSeries (via TR5164-433)

Available in NA, LATAM, EMEA and APAC

**WS4938 1-Button Personal Panic**

- Activation via 1 large, easy-to-use button
- Integrated LED to indicate signal transmission
- Neck strap and multifunction belt clip included
- Reliable 433 MHz technology
- Water resistant
- Full 2-second delay on panic button
- Long-life lithium batteries included
- Optional wireless supervision

Available in NA, LATAM, EMEA and APAC



**WS4949 2-Button Wireless Key**

- 2-button, 3-function wireless key
- Activation via 2 large, scratch-resistant buttons
- Full 3-second delay on panic function
- Integrated LED to indicate signal transmission
- Reliable 433 MHz or 868MHz technology
- Long-life lithium batteries included
- Water resistant

Available in NA, LATAM and APAC



**WS4939 / WS8939 4-Button Wireless Key**

- Durable, scratch-resistant buttons
- 4 programmable function keys
- Long-life lithium batteries included
- Full 3-second delay on panic alarm to reduce false alarms
- Multifunction belt clip included
- Reliable 433 MHz or 868 MHz technology
- Optional generic rubber insert included
- Water resistant

Available in NA, LATAM, EMEA and APAC



**WS4959 5-Button Wireless Key**

- 12 programmable function keys
- Integrated tri-color LED to indicate signal transmission and security modes
- 4 durable, scratch-resistant buttons and center toggle button
- Multifunction belt clip included
- Reliable 433 MHz technology
- Full 3-second delay on panic function
- Long-life lithium batteries included
- Water resistant

Available in NA, LATAM and APAC







WS4913 / WS8913 Wireless CO Detector

- Slim-line design
  - Built-in 85dB alarm at 10 ft (3 m)
  - Malfunction supervision
  - Low sensitivity supervision
  - Electrochemical sensing technology
  - Transmits RF status, low battery and tamper condition
  - Hush feature
  - Wall tamper
  - 4-5 year battery life
- Onboard LEDs indicate:
    - Red – Alarm
    - Yellow – Trouble
    - Green – Power
    - Amber – Warm Up
  - End-of-Life (EOL) indicator (5 years)
  - Low battery supervision
  - Compatible with IMPASSA and PowerSeries v4.5 & higher
  - Reliable 433 MHz or 868 MHz technology

Available in NA, LATAM, EMEA and APAC



WT4901 / WT8901 2-Way Wireless Indoor Siren

- Siren Output – 85dB
  - Siren sounds for alarms, door chimes, entry/exit delay and troubles
  - Transmits RF status, low battery and tamper condition
- Front and back tamper detection
  - Nominal battery life – 1 year
  - Compatible with IMPASSA (433 MHz)
  - Onboard test button

Available in NA, LATAM, EMEA and APAC

WS4936 Wireless Photoelectric Smoke Detector

- Automatic drift compensation
  - Built-in 85dB horn
  - Local test button
  - Low profile design
  - High/Low sensitivity reporting
- Easy-maintenance removable smoke chamber
  - Long-life lithium batteries included
  - UL/ULC listed for residential applications
  - Low battery indication

Available in NA



WT4911 / WT8911 2-Way Wireless Outdoor Siren

- Siren Output – 100dB
  - Siren sounds for alarms and squawks
  - Strobe light functionality for visual indication
  - Provides temperature to WT5500 wire-free keypad
  - Transmits RF status, low battery and tamper condition
- Large print area for company logo
  - Front and back tamper detection IP34 rating
  - Nominal battery life – 2-3 years
  - Compatible with IMPASSA (433 MHz)
  - Remote test capability

Available in NA, LATAM, EMEA and APAC

WS4985 / WS8985 Wireless Flood Detector

- Based on WS4945 wireless door/window contact
  - Water probe through a (1.8 m )6 foot-wire
  - Fully supervised
  - Built-in reed switch
- Normally closed external contact input
  - 1 lithium battery included
  - Case and wall tamper
  - End-of-line resistor
  - 4 year battery life

Available in NA, LATAM, EMEA and APAC



WS4920 / WS8920 Wireless Repeater

- Greatly extends the range of DSC 1-way wireless devices
  - Backward compatible with existing security systems including, IMPASSA, PowerSeries and MAXSYS
  - WS4920 identifies the optimal location for mounting taking in to consideration noise and interference
  - Quick enrolment of DSC 1-way wireless devices
- Status LEDs for AC, battery and RF Jam
  - Up to four repeaters can be installed for each panel/receiver
  - WS4920 supports up to 164 wireless devices
  - Wall and case tamper protection
  - Aesthetically pleasing design

Available in NA, LATAM, EMEA and APAC



**PowerSeries Neo and Alarm.com come together – for the ultimate smart security solution.**



The combination of easy-to-install hybrid scalable security solutions by DSC and smart business solutions by Alarm.com elevate commercial security to a whole new level. With features like video monitoring, automation and energy management you have visibility and control of your business whenever you need it.

**Welcome to Security Redefined.**  
**www.dsc.com**

©2017 Tyco Security Products



# DSC TOUCH

## All-in-One. Always Connected



**7" TouchScreen with built-in camera and compatible with DSC 433 Mhz one-way wireless products**



Please visit [www.dsc.com](http://www.dsc.com)

© 2017 Tyco Security Products

Universal Communicators  
Solutions





3G4000 HSPA Universal Cellular Alarm Communicator

- Compatible with control panels that communicate using the Contact ID format
- Uses HSPA (3G) network for high-speed, reliable and low-cost communications to Sur-Gard System I-IP/II/III/IV/5 receivers
- Activation and initialization via website or mobile interface provided by C24 Communications
- View communicator status directly from your mobile phone to support on-site or remote troubleshooting
- SMS command & control for panel arm/disarm
- 2 on-board outputs
- 2 on-board inputs
- Full event reporting
- Two unique trouble display models
- Advanced carrier selection to secure a suitable cellular connection
- Monitors the panel's attempts to communicate to determine if cellular backup communications are necessary
- Call routing to direct cellular signals to multiple receivers based on dialed number
- Antenna Extension Kits available: GS-8ANTP, GS-15ANTQ, GS-25ANTQ, GS-50ANTQ
- Rogers or AT&T SIM card (included)

Available in NA



GS4005 / 3G4005 Universal Cellular Communicator

- Stand alone and KIT versions
- EN50136 Approved
- Integrated Antenna
- Remote programming by DLS 5
- Communicates directly with the central monitoring station
- 6 programmable terminals (input/output)
- CiD to Voice messages function and CiD to SMS message function
- USB port for local programming;
- Connector for optional external antennas
- Optional Li-Ion Battery for 6 hours autonomy

Available in LATAM, EMEA and APAC



3G4010CF HSPA Universal Wireless Commercial Fire Alarm Communicator


- Uses HSPA (3G) network for high-speed, reliable and low cost communications to an IP receiver
- Automatically switches to 2G (EDGE/GPRS) if 3G service is not available
- Compatible with control panels that communicate using Contact ID or SIA (300 baud) formats
- Full event reporting
- 4 on-board inputs with NC, NO or SEOL supervision
- 4 on-board outputs (open collector)
- Activation and initialization via web-user or mobile interface provided by C24 Communications
- View communicator status directly from your mobile phone to support on-site or remote troubleshooting
- Compatible with Sur-Gard® System I-IP/II/III/IV/5 monitoring station receivers
- Includes UL listed power supply, transformer and 7 Ah rechargeable battery

Available in NA

TL300 Universal Internet Alarm Communicator

- Compatible with most control panels that use the Contact ID format
- Instant, always-on IP communication
- Works over local LAN/WAN network or the Internet
- 128-bit AES encryption (NIST approved)
- Supports DHCP (dynamic IP addresses)
- Low network bandwidth requirements
- Compatible with 10/100BaseT networks
- Reports events to 2 different receiver IP addresses

Available in NA, LATAM, EMEA and APAC



- UL standard & encrypted line security
- 12-24 volt DC support (v1.5 and higher)
- 4 on-board programmable zone inputs and 2 programmable voltage outputs as stand-alone module
- Programmable through the PK5500 LCD keypad or T-Link Console software
- Software upgrades via network
- Compatible with Sur-Gard System I-IP/II/III/IV/5 monitoring station receivers
- Polling and hardware substitution protection

TL300CF Kit

- Commercial fire internet communicator
- Works with any control panel that communicates using Contact ID format
- Configured for standalone commercial fire applications
- Compliant with NFPA72 Editions: 2002, 2007, 2013
- Power supply included
- Compatible with most control panels that use the Contact ID format
- 128-bit AES encryption (NIST approved)
- Supports DHCP (dynamic IP addresses)
- Low network bandwidth requirements
- Reports events to 2 different receiver IP addresses

Available in NA



- UL standard & encrypted line security
- 4 on-board programmable zone inputs and 2 programmable voltage outputs as standalone module
- Programmable through the PK5500 L CD keypad or T-Link Console software
- Software upgrades via network
- Compatible with Sur-Gard System I-IP/II/III/IV/5 monitoring station receivers
- ULC passive or active security levels
- ULC active line security levels A1-A4
- Polling and hardware substitution protection

# Your most valuable tool may be on the web



## The **dsc.com** website



Robust technical library • User and installation manuals • Software  
• Product descriptions • Photography • Application notes  
• Marketing materials • Solutions • Certifications

Visit [dsc.com](http://dsc.com), your complete online resource for DSC product information.

**DSC**  
*From Tyco Security Products*



Hardwired Solutions





Bravo® 6 Twin, Dual-Element, Pet-Immune PIR Motion Detectors

- Digital signal analysis for consistent detection throughout the coverage pattern
- Digital temperature compensation for improved catch performance at critical temperatures
- Patented Multi-Level Signal Processing (MLSP) for accurate detection of human IR energy over a broad range of temperatures
- Pet immunity up to 85 lb (39 kg)
- Optional mounting brackets available: DM-W (wall-mount bracket) or DM-C (ceiling-mount bracket)

Available in NA, LATAM, EMEA and APAC

Model	Description
BV-600	Form 'A' alarm contact
BV-601	Form 'A' alarm contact & tamper switch
BV-602	Form 'C' alarm contact & tamper switch



Bravo® 5 360° Ceiling-Mount PIR Motion Detectors

- Temperature compensation for improved catch performance at critical temperatures
- Patented Multi-Level Signal Processing (MLSP) for accurate detection of human IR energy over a broad range of temperatures
- Sensitivity adjustment to configure the detector for normal or hostile environments
- High-level static and transient protection
- Exceptional white light immunity
- Excellent RF immunity
- Digital signal analysis for consistent detection throughout the coverage pattern

Available in NA, LATAM, EMEA and APAC

PIR only

Model	Description
BV-500	Form 'A' alarm contact
BV-501	Form 'A' alarm contact & tamper switch
BV-502	Form 'C' alarm contact & tamper switch

PIR and Glassbreak

Model	Description
BV-500GB	Form 'A' alarm contact (motion), form 'C' alarm contact (glassbreak)
BV-501GB	Form 'A' alarm contact (motion), form 'C' alarm contact (glassbreak) & tamper switch
BV-502GB	Form 'C' alarm contact (motion), form 'C' alarm contact (glassbreak) & tamper switch

BV-201 Bravo® 201 PIR Motion Detectors

- The Bravo 201 motion detectors feature patented Multi-Level Signal Processing (MLSP) for accurate
- Detection of human IR energy over a broad range of temperatures
- Exceptional catch performance at elevated temperatures
- High-level static and transient protection
- Sensitivity adjustment to configure the detector for normal or hostile environments

Available in NA, LATAM, EMEA and APAC

Model	Description
BV-201	Form 'A' alarm contact
BV-L1	Wall-to-Wall-lens
BV-L2	Corridor lens
BV-L3	Curtain lens
BV-L4	Pet Alley lens



LC-100-PI / LC-120-PI PIR Detector with Pet Immunity

- Form 'A' or 'C' alarm contact and tamper switch
- Digital signal analysis
- Pet immunity up to 55 lb (25 kg)
- Quad Linear Imaging Technology for sharp analysis of body dimensions and differentiation from backgrounds and pets
- Advanced ASIC-based electronics
- Compact design for residential installations
- Adjustable variable pulse count
- PIR sensitivity adjustment
- Installation height is calibration free from 6 ft to 8 ft (1.8 m to 2.4m)
- Available in packages of 6 (LC-100-PI-6PK)
- LC-L1ST bracket available separately
- Corridor lens available separately

Available in NA, LATAM, EMEA and APAC

Model	Description
LC-100-PI-6PK	Form 'A' alarm contact & tamper switch
LC-120-PI	Form 'C' alarm contact & tamper switch





LC-101 PIR Detector with Camera & Pet Immunity

- Form 'A' alarm contact and tamper switch
- Digital signal analysis
- Pet immunity up to 25 kg (55 lb)
- Quad Linear Imaging Technology for sharp analysis of body dimensions and differentiation from backgrounds and pets
- Advanced ASIC-based electronics
- Wide-range operating voltage
- High reliability, trouble-free operation
- User-friendly installation with or without swivel-mount bracket

Available in EMEA

Model	Description
LC-101-CAMCLPAL	Color PAL



LC-102-PIGBSS Glassbreak Detector with Pet Immunity

- Form 'A' alarm contact and tamper switch
- Digital signal analysis
- Slim profile design
- Exceptional white light immunity
- Pet immunity up to 25 kg (55 lb)
- Quad Linear Imaging Technology for sharp analysis of body dimensions and differentiation from backgrounds and pets
- Separate PIR and glassbreak sensitivity adjustment
- Features ABS plastic for shock and impact protection
- 2 independent relay outputs for glassbreak and PIR alarm signals
- Advanced ASIC-based electronics
- LC-L1ST bracket available separately

Available in NA, LATAM, EMEA and APAC

Model	Description
LC-102-PIGBSS	Digital PIR and Glassbreak Detector with Pet Immunity

LC-103-PIMSK, LC-104-PIMW & LC-124-PIMW Dual Technology Motion Detector with Pet Immunity

- Anti-masking (LC-103-PIMSK)
- Form 'A' or 'C' alarm contact and tamper switch
- Digital signal analysis
- Pet immunity up to 55 lb (25 kg)
- Quad Linear Imaging Technology for sharp analysis of body dimensions and differentiation from backgrounds and pets
- Microwave detection based on Doppler concept
- Unique microwave motion sensor module with micro-strip patch antenna
- Advanced ASIC-based electronics Height installation calibration free 2-way PIR/microwave sensitivity adjustment
- User-friendly installation with or without swivel-mount bracket available separately: LC-L1ST

Available in NA and APAC

Model	Description
LC-103-PIMSK-W	Form 'A' 10.525 GHz alarm contact & tamper switch
LC-104-PIMW-W	Form 'A' 10.525 GHz alarm contact & tamper switch
LC-124-PIMW-W	Form 'C' 10.525 GHz alarm contact & tamper switch



LC-105-DGB Glassbreak Detector

- Form 'A' alarm contact and tamper switch
- Digital signal analysis
- Detects the sound of all types of breaking framed glass
- Phased frequency detector sensor
- Able to adjust sound sensors separately
- Ceiling- or wall-mount installation
- Slim profile design
- Features ABS plastic for shock and impact protection

Available in NA, LATAM, EMEA and APAC

Model	Description
LC-105-DGB	Digital Glassbreak Detector





LC-151 Dual-Tech Outdoor Motion Sensor (Single PIR & Microwave) with Adjustable Pet Immunity

- Microwave frequency: 10.525 GHz
- Microwave detection based on Doppler concept
- N.O. & N.C. relays switched at the same time
- Installation height is calibration free from 6 ft to 8 ft (1.8 m to 2.4 m)
- Pet Immune up to 33 lb (15 kg) without pet immunity lens or up to 80 lb (36 kg) when using supplied L C-F1-15X pet immunity lens
- PIR sensitivity adjustment
- MW intensity selection
- Temperature compensation
- Microcontroller signal processing
- Front and back tamper protection
- Unique waterproof and seal plastic design
- Detection range: up to 49 ft (15 m)
- Detects human intruders walking or running
- No maintenance required
- High RFI / EMI immunity
- Protection from: direct sunlight, wind up to 30m/sec, snow and rain, small animals, removal of top cover and removal from mounting bracket
- Rain and dust proof: IP65
- LC-B1-15X wall mount bracket available separately

Available in NA, LATAM and APAC

Model	Description
LC-151	Form 'C' alarm contact and tamper switches



LC-171 Dual-Tech Outdoor Motion Sensor (Double PIR & Microwave) with Pet Immunity

- Microwave frequency: 24.125 GHz
- Microwave detection based on Doppler concept
- N.O. & N.C. Relays switched at the same time
- Pet immunity up to 77 lb (35 kg)
- 16 levels of PIR sensitivity adjustment and 3 microwave sensitivity groups
- Temperature compensation
- Microcontroller signal processing
- Front and back tamper protection
- Audible indication of walk test and intruder detection
- Unique waterproof sealed plastic design
- Detection range: up to 12m (39ft)
- Detect human intruders walking or running
- No maintenance required
- High RFI/EMI immunity
- Protection from: direct sunlight, wind up to 30 m/sec, snow and rain, small animals, removal of the top cover and removal from mounting bracket
- Rain and dust proof: IP65

Available in NA, LATAM, EMEA and APAC

Model	Description
LC-171	Form 'C' alarm contact and tamper switches

Acuity® Glassbreak Detectors

- Omni-directional microphone
- Advanced microprocessor-based glassbreak sensor
- High-level static and transient protection
- High RF immunity with SMD construction
- White noise rejection mechanism
- Installer test mode for glassbreak sensor (AFT-100 tester required)
- Alarm memory (latching LED) for glassbreak sensor
- MOV transient/static protection
- Jumper selectable sensitivity range
- Wall-Mount or Ceiling-Mount version available

Available in NA, LATAM, EMEA and APAC

Wall-Mount

Model	Description
AC-100	Form 'A' alarm contact
AC-101	Form 'A' alarm contact & tamper switch
AC-102	Form 'C' alarm contact & tamper switch

Ceiling-Mount

Model	Description
AC-500	Form 'A' alarm contact
AC-501	Form 'A' alarm contact and tamper switch



DG-50AU Glassbreak Detector

- Clean, modern design blends with any décor
- Advanced signal discrimination for accurate identification of breaking glass
- Resistant to blinding by background noises
- Sensitivity adjustment potentiometer
- Anti-shock design prevents false alarms from mechanical shock
- MOV static/lighting protection
- SMD construction and integral ground shield for high RF immunity

Available in NA, LATAM, EMEA and APAC







AFT-100 Glassbreak Simulator

The AFT-100 glassbreak simulator provides the most reliable and accurate indication of the correct mounting location for the detector. Do not install the detector beyond the maximum recommended range, even if the glassbreak simulator reports additional range. Future changes in room acoustics could reduce any additional range.

Available in NA, LATAM, EMEA and APAC



SS-102 Shock Sensor

- Unique bi-colored LED to indicate minor or major attacks
- Anti-tamper protection
- Moisture-resistant electronics module
- Sensitivity adjustment
- High immunity to low-frequency false alarms and radio interference
- Compatible with all makes of control panels
- SS-102 is able to monitor for minor vibrations (and count them to a preset limit) and for major attacks at the same time

Available in NA, LATAM, EMEA and APAC

FSA-210/410 Wired Photoelectric Smoke Detectors

- Automatic drift compensation
- Built-in, dual-sensor heat detector (option)
- Built-in 85dB horn (option)
- Easy-maintenance removable smoke chamber
- Interconnectable using PRM-2W/4W polarity reversal modules
- Low profile design
- Local test button
- RM-2 end-of-line power supervisory relay (4-wire detectors only) available separately

Available in NA, LATAM, EMEA and APAC



FSA-210

Model	Description
FSA-210(x)*	2-wire photoelectric smoke detector
FSA-210(x)T*	2-wire photoelectric smoke detector w/ heat detector
FSA-210(x)ST*	2-wire photoelectric smoke detector w/ integral sounder & heat detector
FSA-210(x)RT*	2-wire photoelectric smoke detector w/ aux. relay & heat detector

FSA-410

Model	Description
FSA-410(x)*	4-wire photoelectric smoke detector
FSA-410(x)T*	4-wire photoelectric smoke detector w/ heat detector
FSA-410(x)RT*	4-wire photoelectric smoke detector w/ aux. relay & heat detector
FSA-410(x)S*	4-wire photoelectric smoke detector w/ integral sounder
FSA-410(x)ST*	4-wire photoelectric smoke detector w/ integral sounder & heat detector
FSA-410(x)RST*	4-wire photoelectric smoke detector w/ integral sounder, aux. relay & heat detector

\*Legend (x) = 'A' Canadian model number (ULC listed) | (x) = 'B' U.S. model number (UL listed) | 'C' Canadian model number (EU listed).

Not all models available in all regions

FSB-210 Series Addressable Photoelectric Smoke Detectors

FSB-210B (without Heat Sensor)

FSB-210BT (with Heat Sensor) – Fixed Heat With Rate Of Rise (rate of rise feature not UL listed)

- Automatic drift compensation
- Easy-maintenance removable smoke chamber
- Self diagnostics

Not available in Canada





AML-770B Loop Isolator Module

- Isolate burglary detectors from fire detectors on the same wire run

Available in NA, LATAM, EMEA and APAC



AMX-400 Loop Repeater/Isolator Module

- Can be used to repeat and re-power the AML loop to allow for longer wire runs
- Requires 12 VDC power source
- Will isolate the wire run in the event of a problem
- Provides additional 170 mA

Available in NA, LATAM, EMEA and APAC



Addressable Contact Modules

Model	Description
AMP-700	Door/Window contact with built-in reed switch
AMP-701	Door/Window contact with normally closed external contact input
AMP-702	Fire point module with normally open, EOL resistor supervised external contact input
AMP-704	4-zone door/window contact with normally closed, single or double EOL inputs

AMA-100 Addressable Glassbreak Detector

- Based on the Acuity® hardwire glassbreak detector
- Detects all types of breaking glass: plate, laminated, safety and tempered
- Can be tested using the glassbreak simulator (AFT-100)
- Built-in tamper switch

Available in NA, LATAM, EMEA and APAC



AMB-300 Addressable Passive Infrared Detector

- Patented MLSP (Multi-Level Signal Processing)
- Interchangeable lenses: wall-to-wall lens (standard), curtain lens, pet-immune lens and corridor lens
- Built-in tamper switch
- Based on the Bravo® 3 hardwire motion detector

Available in NA, LATAM, EMEA and APAC



AMB-500 Addressable Ceiling-Mount Passive Infrared Detector

- Based on the Bravo® 5 hardwire motion detector
- Built-in tamper switch
- Coverage diameter based on mounting height

Available in NA, LATAM, EMEA and APAC



AMB-600 Addressable Pet-Immune Passive Infrared Detector

- Based on the Bravo® 6 hardwire motion detector
- Patented MLSP (Multi-Level Signal Processing)
- Provides pet immunity up to 85 lb (39 kg)
- Built-in tamper switch

Available in NA, LATAM, EMEA and APAC



# Sur-Gard System 5 with visual verification support.

A powerful, yet more compact virtual receiver.



Building on the Sur-Gard legacy, SG-System 5 supports alarm verification solutions to significantly reduce costs associated with false alarms.

The *more compact footprint* facilitates space management while offering the *highest account density* per U rack available in the industry.

Built-in redundancy for power and auto-switching assures continuous performance of all peripheral devices connected to the output ports.

**Industry-leading reliability and unbeatable capacity, all in a compact receiver.**



**SUR-GARD**  
From Tyco Security Products

For more information on products featured here call 1-800-418-7618 or visit [www.sur-gard.com](http://www.sur-gard.com)

Central Monitoring  
Station Solutions





### SG-SYSTEM I / SG-SYSTEM I-IP Dual Phone Line with Optional IP Receiver

- Multi-format receiver
- Integrated scheduled receiver line card testing
- Up to 63 different profiles and up to eight different handshakes per profile
- 500-event memory buffer on each individual POTS channels
- Patented ANI and DNIS reception, Automatic Handshake Selection (AHS), Caller ID capability and virtual configurations
- Continuous verification of computer (automation) connection
- One parallel, one serial, one USB, one TCP/IP printer port available
- One serial, one TCP/IP automation port available
- One USB, one TCP/IP console port available
- Non-volatile RAM for programming and event buffer
- Optional support for 512 IP Communicators (SG-SYS1512IP)
- Rack mount in standard 19-inch rack with the SG-SII-RMK
- 128 Bit AES encryption over IP
- Menu-driven, 40-character, 2-line LCD display with blue backlighting provides instruction when in manual mode
- 4 buttons for manual programming and acknowledgement of alarm signals when in manual mode
- Universal power supply compatible with 110/220 50 Hz/60 Hz
- Onboard flash memory and DSP for future software upgrades and enhancements


Available in NA, LATAM, EMEA and APAC



### SG-SYSTEM II Single-Line IP Receiver

- Value-priced remote monitoring solution ideal for lower-volume applications
- Supports up to 512 supervised and up to 1,536 IP communicator accounts (all DSC communicators)
- Rack mount in standard 19-inch rack with the SG-SII-RMK
- TCP/IP, USB, serial outputs to automation software
- 128-bit AES encryption
- Works over local LAN/WAN network as well as the Internet
- Polling and hardware substitution protection
- Compatible with 10/100BaseT networks
- Fully programmable via SG-Systems Console software
- Menu-driven, 40-character, 2-line LCD display with blue backlighting provides instruction when in manual mode
- 4 buttons for manual programming and acknowledgement of alarm signals when in manual mode
- Universal power supply compatible with 110/220 50 Hz/60 Hz
- Onboard flash memory and DSP for future software upgrades and enhancements
- Additional 1,536 IP communicator accounts available with license key upgrade (SG-SYS21536IP)

Available in NA, LATAM, EMEA and APAC



### SG-SII-RMK Rack Mount Kit

- Rack mount kit for SG-SYSTEM I-IP or S G-SYSTEM-II to mount in any standard 48.26 cm (19") rack

Available in NA, LATAM, EMEA and APAC

### SG-SYSTEM III Virtual Receiver

- Up to 24 line cards per System III receiver SG-DRL3IP, SG-DRL3E or SG-DRL3-2L
- Fully "hot-swappable" modules
- Fully programmable via SG-Systems Console software
- Eliminates fixed-line hunt groups
- Integrated scheduled receiver line card testing
- Blocks unwanted communications
- Upgradeable flash memory
- Automation output over TCP/IP or RS-232

Available in NA, LATAM, EMEA and APAC



### System IV IP Receiver

- Supports over 120 communication formats in small footprint
- Auto-switching redundancy for power and to output peripherals
- Fully 'hot swappable' modules
- Supports up to 24 line cards – IP or PSTN
- 'Flash' download for software updates for lines cards and CPM
- Robust built-in diagnostic software
- Supports an AHS (Automatic Handshake Table) of 250,000 entries.
- Expandable to 500,000 with a separate license key
- SG-CPM4-250KAHS - License Key for 250K AHS Upgrade
- Supports up to 9216 IP accounts per SG-DRL4-IP

Available in NA



### SG-System 5 IP Receiver

- 4U in height (half the height of a redundant System III)
- Integrated redundancy for CPM's automation, power supplies and LCD touch screen interface
- Support for up to 24 IP line cards, expandable to 1,474,560 IP accounts\*
- Single and Dual PSTN line cards with support for 150+ communication formats\*
- Split Reporting and Multi-Port automation modes add scalability and redundancy to automation connections
- Lockable AHS table format and handshake options offer increased control of PSTN communication
- Integration with automation software for visual verification
- Ability to view visual verification via SG-Systems Console (license required)

Available in NA, LATAM, EMEA and APAC



\*Product and Feature availability varies by region

### SG-DRL5-IP Line card

- 512-event memory buffer/card
- 128-bit AES encryption
- Anti-hack design
- Compatibility with all DSC IP Alarm Communicators (Cellular or Ethernet) and licensed partners
- 512 visual verification IP accounts
- 512 supervised IP accounts
- 3,072 unsupervised IP accounts
- Additional IP accounts can be added (up to 61,440) via license keys

Available in NA, LATAM, EMEA and APAC



### A World Class Service Agreement Program for Ultimate Reliability

As the world leader in Central Monitoring Station equipment, Sur-Gard is committed to ensuring on-going satisfaction to customers worldwide who have made Sur-Gard the brand of choice for alarm receiving equipment. The System III /IV and 5 offer a full Service Agreement Program that provides exclusive benefits, such as:

- 5% off all future hardware purchases
- Access to Monthly Sur-Gard Webinars
- Unlimited Firmware upgrades
- Free 30 Day Loaner Receiver Program
- 24hr/7 days a week Tech Support
- Advanced Hardware Replacement Program

This unique approach demonstrates Sur-Gard's commitment to ensuring reliability that is required by all components that make up today's Central Monitoring Station.

Contact DSC Customer Service at 1-800-418-7618 to inquire about the Sur-Gard Service Agreement Program for additional exclusive benefits.

Some products are not available in all countries. Please contact your local distributor or refer to [www.dsc.com](http://www.dsc.com) for the most current approval listings.

DLS 5 Downloading Software

DLS 5 is future-ready! Primed for compatibility with future technologies, DLS 5 Downloading Software offers user-friendly interfaces. It runs on Microsoft's powerful. NET Framework 4.0 and now uses an ultra-light SQLite database. Installation is quick and easy. All necessary software packages will be installed automatically during the DLS 5 installation process.

NOTE: SQLite is a light-weight database which does not require any database engine installation.

Features:

- Supports a wide array of DSC products, from the latest released products back to PowerSeries v4.1
- Tightly integrated with C24 Communications to allow cellular connections
- Available in "Workgroup" mode, enabling larger organizations to host a centralized support database
- Optimized communication workflows allowing scheduled communications, unattended communications and complete communication queue
- Packed with record keeping & convenience features to meet all your business needs

Supported Database:

- SQLite

Minimum System Requirements:

- 1GHz Pentium III compatible processor; 1GB of RAM; up to 2GB of available disk space

Available in NA, LATAM, EMEA and APAC



WebSA – System Administrator Software

To perfectly complement the alarm industry's most flexible hybrid intrusion system, DSC has released revolutionary software – WebSA System Administrator. Giving administrative users unprecedented ability to manage, monitor and control user functionality of their security system, WebSA System Administrator features user-friendly and intuitive interfaces with 'Real-Time' Dashboards.

Minimum System Requirements:

- 1GHz Pentium III compatible processor; 1GB of RAM; up to 2GB of available disk space
- Please refer to [www.dsc.com](http://www.dsc.com) for Operating System Support

Available in NA, LATAM, EMEA and APAC





## Routine System Management (RSM)

PowerSeries Neo’s Routine System Management is a revolutionary remote inspection tool leveraging comprehensive diagnostic data to reduce operating costs by dramatically reducing the number of truck rolls required for diagnostics and maintenance of the security system. Using a simple yet highly efficient workflow process which encompasses steps such as Automatic Connection, Data Collection, Evaluation and Resolution, RSM removes, wherever possible, the need for site visits.

### Features:

- Automatic RSM inspections
- Report generation
- Ability to set frequency intervals for RSM inspections
- RSM report history
- RSM report results for “Pass” or “Service Required” status
- Ability to approve or fail RSM reports
- Ability to set a new baseline for system diagnostic values
- Hardware diagnostics
- Wireless device network diagnostics
- Virtually monitor keypad mode for viewing the actions on the physical keypad in real-time
- RSM operator permissions
- Ability to export RSM report into XML or PDF file

Available in NA, LATAM, EMEA and APAC



DSC understands that security dealers everywhere need more than just great products, they deserve exceptional service and support as well. That is why we have committed resources to ensure we’re in a position to help our customers as needed.

## DSC Customer Service and Support

A dedicated team of Technical Support, Customer Service and Sales Support Representatives are available to provide security professionals with valuable expertise and in-depth product knowledge. The Customer Service and Support Center offers extended hours of services and access to all departments within DSC with multilingual support.


For any inquiries, general product information or the location of the nearest DSC distributor, please call 1 888.888.7838 (Toll Free) / +1 905.760.3000 or email us at [info@dsc.com](mailto:info@dsc.com).

Global tech support contact information:

North America: +1-800-387-3630

Latin America: +1-905-760-3000

EMEA & AsiaPac: Toll Free 800-22558926



## DSC Marketplace

The DSC Marketplace is your primary method for ordering product-specific literature, associated marketing support materials and promotional items. To access this great service, please visit [www.dscmarketplace.com](http://www.dscmarketplace.com) and complete the short registration form. Your account will be activated within 48 hours allowing you to start browsing the site at your convenience. To ensure proper materials are being ordered, you can view thumbnail pictures as well as download PDF files of all items. For more information please visit [www.dscmarketplace.com](http://www.dscmarketplace.com).

## www.dsc.com

The DSC website is an intuitive, easy-to-navigate resource that provides security professionals with access to a wealth of product-specific information. Password-protected areas are tailored specifically for security dealers and offer the latest news on DSC products, corresponding events and launches, the latest technical support materials and diagnostic tools, and helpful industry and association links. Downloadable PDF versions of all DSC sales and specification sheets, images, end-user manuals, architect and engineer specifications, plus the complete DSC product catalog can be found on the website. Visit [www.dsc.com](http://www.dsc.com) to learn more.



Since 1998, C24 Communications has been activating and administering cellular devices (DSC branded Alarm Communicators) for security alarm dealers in North America. The units are activated through a mobile interface or via C24 Communications’ web portal.

These secure interfaces allow for the activation, editing and deactivation of accounts, the retrieval of device status and programming or modification of communicator options.

For more information on C24 Communications, please visit [www.connect24.com](http://www.connect24.com).



Product name	Page #
3G2055	38
3G2060(R)	29
3G2080E	11
3G4000	46
GS4004 / 3G4005	46
3G4010CF	46
3G8055(I) / CD8055(I)	38
3G8080(I) / CD8080(I)	11
<b>Acuity®</b>	<b>55</b>
AFT-100	56
AMA-100	59
AMB-300	59
AMB-500	59
AMB-600	59
AML-770B	58
AMX-400	58
<b>C24 Communications</b>	<b>66</b>
<b>DG-50AU</b>	<b>55</b>
DLS 5	65
<b>EV-DW4917</b>	<b>39</b>
EV-DW4927SS	40
EV-DW4975 / EV-DW8975	39
<b>FSA-210</b>	<b>57</b>
FSA-210/410	57
FSA-410	57
FSB-210BT	57
FSB-210B	57
FSB-210	57
<b>HS2ICN</b>	<b>8</b>
HS2ICNP	8
HS2ICNRFPx	8
HS2ICNRFx	8
HS2LCD	9
HS2LCDP	9
HS2LCDRFPx	9
HS2LCDRFx	9
HS2LCDWFPVx	8
HS2LCDWFPx	8
HS2LCDWFx	8
HS2TCHP	9
HS2016-4	6
HS2016	6
HS2032	6
HS2064	6
HS2128	6
HSM2HOSTx	10
HSM2108	10

Product name	Page #
HSM2204	10
HSM2208	10
HSM2300	10
HSM2955(R)	10
<b>IT-100</b>	<b>27</b>
IT-230 RS-422	27
<b>LC-100-PI / LC-120-PI</b>	<b>51</b>
LC-101	52
LC-102-PIGBSS	52
LC-103-PIMSK, LC-104-PIMW & LC-124-PIMW	53
LC-105-DGB	53
LC-151	54
LC-171	54
LCD4501	30
<b>MaxKit</b>	<b>30</b>
Mini Prox Tag	8
<b>PC1616</b>	<b>20</b>
PC1832	20
PC1864	20
PC4020	30
PC4108A / PC4116	32
PC4204 / PC4204CX	31
PC4216	31
PC4401	31
PC4632 / PC4664	32
PC4820	31
PC5100	26
PC5108	26
PC5200 / PC5204	26
PC5208	26
PC5320	26
PC5400	27
PC5950	27
PC5961E	28
PC5962	28
PC5964E	28
PCL-422	10
PGx901	18
PGx904P	12
PGx905	17
PGx911	18
PGx913	17
PGx914	14
PGx916	16
PGx920	18
PGx922	14
PGx924	13

Product name	Page #
PGx926	16
PGx929	15
PGx934P	13
PGx935	16
PGx938	15
PGx939	15
PGx944	14
PGx945	12
PGx949	15
PGx974P	14
PGx975	12
PGx984P	13
PGx985	17
PGx994	14
PK5500	22
PK5501	22
PK5508	23
PK5516	23
PowerSeries Neo Feature Comparison Chart	7
PTK5507	23
<b>Readers</b>	<b>33</b>
RF4164-433	32
RF5132-433 / RF5132-868	28
RFK5500	22
RFK5501	22
RFK5508	23
RFK5516	23
RFK5564	22
Routine System Management (RSM)	66
SCW9055 / SCW9057	36
SCW9067	36
<b>SurGard</b>	
SG-DRL5-IP	63
SG-SII-RMK	62
SG-System 5	63
SG-SYSTEM III	63
SG-SYSTEM II	62
SG-SYSTEM IV	63
SG-SYSTEM I / SG-SYSTEM I-IP	62
SS-102	56
A World Class Service Agreement Program	63
<b>Bravo</b>	
Bravo® 5	50
Bravo® 6	50
BV-201	51

Product name	Page #
<b>TL250</b>	<b>32</b>
TL260(R)	29
T280E / TL280RE	11
TL300CF	47
TL300	47
TL2603G(R)	29
TL2803GE / TL2803GRE	11
TR5164-433	28
T-REX	33
<b>WebSA – System Administrator Software</b>	<b>65</b>
WS4904P	40
WS4904 / WS8904	40
WS4913 / WS8913	42
WS4920 / WS8920	43
WS4936	42
WS4938	41
WS4939 / WS8939	41
WS4945* / WS8945	39
WS4949	41
WS4959	41
WS4965	39
WS4985 / WS8985	42
WT4901 / WT8901	43
WT4911 / WT8911	43
WT4989 / WT8989	41
WT5500	24, 37
WTK5504	24, 37



# DSC

*From Tyco Security Products*

For more information on the products featured here or on any other DSC products please call: **1 905.760.3000 | 1 888.888.7838**  
Toll-free in US & Canada

E-mail us at **info@dsc.com**  
or contact your DSC Account Representative

Please visit us at **www.dsc.com**

© 2017 Tyco Security Products

